

SECTION .1100 - GENERAL PERMIT FOR CONSTRUCTION OF BULKHEADS AND ~~THE PLACEMENT OF RIPRAP~~ REVETMENTS FOR SHORELINE PROTECTION IN ESTUARINE AND PUBLIC TRUST WATERS AND OCEAN HAZARD AREAS

15A NCAC 07H .1101 PURPOSE

A permit under this Section shall allow the construction of bulkheads and ~~the placement of~~ riprap revetments for shoreline protection in the public trust waters and estuarine waters AECs according to authority provided in Subchapter 07J .1100 and according to the Rules in this Section. This permit shall not apply to shoreline protection along the oceanfront or to waters and shorelines adjacent to the Ocean Hazard AEC with the exception of those shorelines that feature characteristics of the Estuarine Shoreline AEC. Such features include the presence of wetland vegetation, lower wave energy and lower erosion rates than the adjoining Ocean Erodible Area.

History Note: Authority G.S. 113A-107(a); 113A-107(b); 113A-113(b); 113A-118.1; 113A-124;
Eff. March 1, 1984;
Amended Eff. April 1, 2003.

15A NCAC 07H .1102 APPROVAL PROCEDURES

(a) An applicant for a General Permit under this Subchapter shall contact the Division of Coastal Management and request approval for development. The applicant shall provide information on site location, dimensions of the project area, and ~~his~~ the applicant's name and address.

(b) The applicant shall provide:

- (1) confirmation that a written statement has been obtained signed by the adjacent riparian property owners indicating that they have no objections to the proposed work; or
- (2) confirmation that the adjacent riparian property owners have been notified by certified mail of the proposed work. The notice shall instruct adjacent property owners to provide written comments on the proposed development to the Division of Coastal Management within ten (10) days of receipt of the notice, and, indicate that no response shall be interpreted as no objection. The Division of Coastal Management ~~DCM staff~~ shall review all comments and determine, based on their relevance to the potential impacts of the proposed project, if the proposed project can be approved by a General Permit. If the Division of Coastal Management ~~DCM staff~~ determines that the project exceeds the guidelines established by the General Permit Process, DCM shall notify the applicant that ~~he must submit~~ an application for a major development permit shall be required.

(c) No work shall begin until an on-site meeting is held with the applicant and a Division of Coastal Management representative so that the proposed ~~bulkhead~~ alignment may be ~~appropriately~~ marked. Written authorization to proceed with the proposed development shall be issued if the Division representative finds that the application meets all the requirements of this Subchapter. Construction of the bulkhead or riprap revetment structure shall be completed within 120 days of the issuance of the general authorization or the authorization shall expire and it shall be necessary to re-examine the alignment to determine if the general authorization may be reissued.

History Note: Authority G.S. 113A-107(a); 113A-107(b); 113A-113(b); 113A-118.1; 113A-124;
Eff. March 1, 1984;
Amended Eff. October 1, 2007; September 1, 2006; January 1, 1990; December 1, 1987.

15A NCAC 07H .1103 PERMIT FEE

The applicant shall pay a permit fee of two hundred dollars (\$200.00) for riprap revetments ~~and bulkhead structures~~ sited at or above normal high water or normal water level, or a permit fee of four hundred dollars (\$400.00) for ~~bulkhead and~~ riprap revetments structures sited below normal high water or normal water level. The applicant shall pay a permit fee of four hundred dollars (\$400.00) for bulkheads. Permit fees shall be paid by check or money order payable to the Department.

History Note: Authority G.S. 113A-107; 113A-113(b); 113A-118.1; 113A-119; 113-119.1; 113A-124;
Eff. March 1, 1984;
Amended Eff. September 1, 2006; August 1, 2000; March 1, 1991.

15A NCAC 07H .1104 GENERAL CONDITIONS

(a) This permit authorizes only the construction of bulkheads and ~~the placement of~~ riprap revetments conforming to the standards herein.

- (b) Individuals shall allow authorized representatives of the Department of Environment, ~~Health~~, and Natural Resources to make periodic inspections at any time deemed necessary in order to ~~ensure~~ be sure that the activity being performed under authority of this general permit is in accordance with the terms and conditions prescribed herein.
- (c) There shall be no ~~significant~~ interference with ~~the navigation or~~ use of the waters by the public by the existence of the bulkhead or the riprap revetment authorized herein. Bulkheads and riprap revetments authorized in this Rule shall not interfere with the established or traditional rights of navigation of the waters by the public.
- (d) This permit ~~shall will~~ not be applicable to proposed construction where the ~~Department~~ Division of Coastal Management has determined, based on an initial review of the application, that notice and review pursuant to G.S. 113A-119 is necessary because there are unresolved questions concerning the proposed activity's impact on adjoining properties or on water quality; air quality; coastal wetlands; cultural or historic sites; wildlife; fisheries resources; or public trust rights.
- (e) This permit ~~shall does~~ not eliminate the need to obtain any other required state, local, or federal authorization.
- (f) Development carried out under this permit ~~shall must~~ be consistent with all local requirements, AEC rules, and local land use plans current at the time of authorization.

History Note: Authority G.S. 113A-107(a); 113A-107(b); 113A-113(b); 113A-118.1; 113A-124;
Eff. March 1, 1984;
Amended Eff. May 1, 1990; December 1, 1987;
RRC Objection due to ambiguity Eff. May 19, 1994;
Amended Eff. August 1, 1998; July 1, 1994.

15A NCAC 07H .1105 SPECIFIC CONDITIONS

- ~~(a) This general permit is applicable only along shorelines void of wetland vegetation including marsh grass and wooded swamp, or where all construction is to be accomplished landward of such vegetation.~~
- ~~(b) Bulkheads and riprap material shall be positioned as follows:~~
- ~~(1) Bulkheads shall be positioned so as not to exceed more than an average distance of 2 feet waterward of the normal high water mark, or the normal water level contour, whichever is applicable. In no case shall the bulkhead be positioned more than 5 feet waterward of the normal high water or normal water level contour at any point along its alignment.~~
- ~~(2) Riprap shall be positioned so as not to exceed a maximum of 5 feet waterward of the mean high water mark or normal water level contour at any point along its alignment. Where there is an existing bulkhead structure, riprap shall be allowed to extend a maximum of 10 feet offshore. This location standard shall take into consideration the height of the area to be protected (i.e. bulkhead height, water depth) and the alignment shall allow for a slope no flatter than 2 feet horizontal per 1 foot vertical and no steeper than 1½ feet horizontal per 1 foot vertical.~~
- ~~(c) Along shorelines within upland basins, canals, and ditches, bulkheads or riprap material must be positioned so as not to exceed more than an average distance of 5 feet waterward of the normal high water mark or the normal water level contour, whichever is applicable. In no case shall the bulkhead or riprap be positioned more than 10 feet waterward of the normal high water or normal water level contour at any point along its alignment. For the purpose of these Rules, the Atlantic Intracoastal Waterway (AIWW) is considered a natural shoreline and development shall occur as described in 7H .1105(b).~~
- ~~(d) Construction authorized by this general permit shall be limited to a maximum shoreline length of 500 feet.~~
- ~~(e) All backfill material shall be obtained from an upland source.~~
- ~~(f) The bulkhead shall be constructed, or the riprap shall be in place prior to any backfilling activities.~~
- ~~(g) The bulkhead or riprap shall be structurally tight so as to prevent seepage of backfill materials through the structure.~~
- ~~(h) Riprap material shall be free from loose dirt or any other pollutant. It shall be of a size sufficient to prevent its movement from the site by wave or current action.~~
- ~~(i) Riprap material shall consist of clean rock or masonry materials such as but not limited to granite or broken concrete. Materials such as tires, car bodies, scrap metal, paper products, tree limbs, wood debris, organic material or similar material, are not considered riprap.~~
- ~~(j) The bulkhead shall be solid and constructed of treated wood, concrete slabs, metal sheet piles or other suitable materials approved by department personnel. No excavation is permitted except for that which may be required for~~

~~the construction of the bulkhead wall, riprap, deadmen cables, etc. This permit does not authorize any excavation waterward of the approved alignment.~~

~~(k) Bulkheads or riprap shall not extend beyond established alignments nor restrict the original width of the canal or basin.~~

~~(l) If one contiguous acre or more of property is to be excavated or filled, an erosion and sedimentation control plan shall be filed with the Division of Land Resources, Land Quality Section, or appropriate local government having jurisdiction. This plan shall be approved prior to commencing the land-disturbing activity.~~

(a) Along shorelines void of wetland vegetation:

(1) New bulkheads shall have an average approximation of normal high water or normal water level. The bulkhead position shall not exceed a distance of 5 feet waterward of normal high water or normal water level at any point along its alignment.

(2) New bulkheads or riprap revetments on shorelines within manmade upland basins, canals, and ditches, shall be positioned so as not to exceed an average distance of two (2) feet and maximum distance of five (5) feet waterward of normal high water or normal water level.

(3) When replacing an existing bulkhead, the new alignment shall be positioned so as not to exceed a maximum distance of two (2) feet waterward of the current bulkhead alignment. To tie into a like structure on the adjacent property, replacement bulkhead position shall not exceed a maximum distance of five (5) feet waterward of the current bulkhead alignment. When replacing a bulkhead where lands landward of the bulkhead were lost in the last year, bulkheads shall be positioned a maximum of two (2) feet waterward of the original/existing alignment.

(4) Riprap revetments shall be positioned so as not to exceed a maximum distance of 10 feet waterward of the normal high water or normal water level at any point along its alignment

(b) Along shorelines with wetland vegetation, bulkheads and riprap revetments shall be positioned so that all construction is to be accomplished landward of such vegetation.

(c) Bulkheads shall be constructed of vinyl, or steel sheet pile, concrete, stone, timber, or other suitable materials approved by the Division of Coastal Management.

(d) Riprap revetments shall be constructed of granite, marl, concrete without exposed rebar, or other suitable materials approved by the Division of Coastal Management.

(e) Revetment material shall be free from loose dirt or other pollutants

(f) Revetment material shall be of sufficient size to prevent movement from the site by wave action or currents.

(g) Construction design for riprap revetments shall take into consideration the height of the area to be protected (i.e. bulkhead height, escarpment height, water depth) and the alignment shall allow for a slope no flatter than three (3) feet horizontal per one (1) foot vertical and no steeper than 1 ½ feet horizontal per one (1) foot vertical.

(h) All backfill material shall be obtained from an upland source pursuant to 15A NCAC 07H .0208. The bulkhead or riprap revetment shall be constructed prior to any backfilling activities and shall be structurally tight so as to prevent seepage of backfill materials through the structure.

(i) No excavation, grading or fill shall be permitted except for that which may be required for the construction of the bulkhead and/or riprap revetment. This permit shall not authorize any excavation waterward of the approved alignment.

(j) Runoff from construction shall not visibly increase the amount of suspended sediments in adjacent waters. Appropriate sedimentation and erosion control devices, measures or structures shall be implemented to ensure that eroded materials do not enter adjacent wetlands, watercourses and property (e.g. silt fence, diversion swales or berms, sand fence, etc.).

(k) If one contiguous acre or more of property is to be excavated or filled, an erosion and sedimentation control plan shall be filed with the Division of Land Resources, Land Quality Section, or appropriate local government having jurisdiction. This plan shall be approved prior to commencing the land-disturbing activity.

(l) For the purpose of these Rules, the Atlantic Intracoastal Waterway (AIWW) is considered a natural shoreline.

(m) Construction authorized by this general permit shall be limited to a maximum shoreline length of 500 feet.

History Note: Authority G.S. 113A-107(a); 113A-107(b); 113A-113(b); 113A-118.1; 113A-124; Eff. March 1, 1984; Amended Eff. April 1, 2005; December 1, 1991; January 1, 1989; December 1, 1987.