DEQ Public Meeting—Bladen County February 18, 2019

Chemours - Fayetteville Works Draft Air Permit Modification to Reduce PFAS Emissions

Heather Sands, PE Chemical Engineer Permitting Section



Chemours Air Quality Permit Application to Install Thermal Oxidizer/Scrubber System

- Project Background
- Permit Requirements
- Compliance Methods: Testing, Monitoring, Recordkeeping, Reporting
- Timeline



Project Background

April 2018

- DAQ
 Notification
- Chemours
 commitment
 to 99%
 reduction of
 GenX
 emissions
 from baseline

July 2018

 At DAQ request, Chemours submittal of Permit Application to incorporate 99 percent reduction of GenX emissions

November 2018

Proposed
 Consent Order
 signed to
 formalize the
 April 27th
 commitment to
 reduce air
 emissions

January 2019

- Permit drafted to incorporate proposed consent order
- Public Comment Period Begins for Draft Air Permit



Draft Permit Requirements

GenX Facility-wide Limit: 23.027 pounds per year

Thermal Oxidizer/ Scrubber System

Carbon Absorbers

Enhanced Leak
Detection and Repair

- * 99.99% Emission Reduction of all PFAS, including GenX Compounds
- * Replacing existing scrubbers

- * Installed in May 2018
- * Control Vinyl Ethers North indoor fugitive emissions and PPA process

- * Designed to detect leaks sooner and at lower concentrations
- * Increased inspection locations
- *Replacement/improvement of components with low-E technology

Compliance Methods

- Initial Performance Tests
- Annual Performance Tests
- Inspection and Monitoring
- Calculation of facility-wide emissions
- Recordkeeping
- Reporting
- Onsite Inspections



Compliance Methods – Thermal Oxidizer/Scrubber System

Initial Emissions Testing

- Confirm system achieves 99.99% emission reduction
- Establish Operating Parameters

Continuous Compliance Monitoring

- Oxidizer: Firebox temperature and volumetric flowrate at the oxidizer inlet
- Scrubber: pH and flowrate of scrubbing liquid

Annual Emissions Testing

- Ensure proper operation of oxidizer and scrubber
- Establish/confirm operating parameters



Compliance Methods – Carbon Adsorbers

Quarterly Emissions Testing

- Required quarterly to determine carbon replacement schedule and operating parameters
- Establish post-control emissions

Continuous Monitoring

 Hours of operation or production rate or other DAQ-approved parameter

Annual Emissions Testing

Ensures that carbon adsorbers continue to operate in compliance



Enhanced Leak Detection and Repair

Approved Plan will address:

- Pressure Testing 0.5 psig pressure drop; 30-min intervals
- Enhanced audial, visual, olfactory inspections
- Instrument monitoring
- Identification and tagging of additional LDAR components
- Enhanced area monitoring
- Replacement or improvement program for valves and connectors



Additional Compliance Requirements

- Shutdown and Malfunction Plan
 - > Thermal Oxidizer/Scrubber System and Carbon Adsorbers
 - ➤ Approval from DAQ required
 - > Requires sources routed to control devices to be shut down if the control device malfunctions
 - > Establishes how Chemours will maintain the control devices to minimize malfunctions
- Recordkeeping
 - > All records necessary to determine compliance with emission limit
 - > Testing results
 - ➤ Monitoring data
 - > Production data and hours of operation
 - > Inspections
 - ➤ Malfunction events
- Onsite Inspections
- Reports
 - > Semiannual basis
 - ➤ Ongoing requirement to disclose



Estimated Timeline

- Public Comment Period began January 18th
- Comment period closes on February 22nd.
- After this meeting we will be holding a Public Hearing on the Air Permit
- Hearing Officer's Report due 30 days after the close of today's hearing
- Director's Final Permitting Action (i.e., issue or deny) expected end of March/beginning of April



Contact Information

Heather Sands

Permit Engineer

heather.sands@ncdenr.gov

919-707-8725

Gary Saunders

Supervisor, Stationary Source

Compliance Branch

gary.saunders@ncdenr.gov

919-707-8413

More Information Available Online:

https://deq.nc.gov/news/hot-topics/genx-investigation

