EROSION and SEDIMENTATION CONTROL PLAN PRELIMINARY REVIEW CHECKLIST

In order to comply with G.S. 113A, Article 4 and 15A NCAC 04, see below for items routinely needed for review of an erosion and sedimentation control plan. Some items may not be applicable to every plan, depending on the specific site conditions:

NPDES Construction Stormwater General Permit NCG010000	
Designation on the plans where the 7 or 14 day ground stabilization roughly Design of basins with one acre or more of drainage area for surface with the control of the con	
LOCATION INFORMATION	Name and classification of receiving water course or name of
Project location & labeled vicinity map (roads, streets, landmarks) North arrow and scale	municipal operator (only where stormwater discharges are to occur <u>STORMWATER CALCULATIONS</u>
Identify River Basin.	
Provide a copy of site located on applicable USGS quadrangle and NRCS Soils maps if it is in a River Basin with Riparian Buffer requirements.	Pre-construction runoff calculations for each outlet from the site (a peak discharge points). Be sure to provide all supporting data for the computation methods used (rainfall data for required storn
GENERAL SITE FEATURES (Plan elements)	events, time of concentration/storm duration, and runof coefficients).
Property lines & ownership ID for adjoining properties Existing contours (topographic lines) Proposed contours	 Design calculations for peak discharges of runoff (including the construction phase & the final runoff coefficients for the site) Design calcs for culverts and storm sewers (include HW, TW and outlet velocities)
Limits of disturbed area (provide acreage total, delineate limits, and label). Be sure to include all access to measures, lots that will be	Discharge and velocity calculations for open channel and ditcl flows (easement & rights-of-way)
disturbed, and utilities that may extend offsite. Planned and existing building locations and elevations Planned & existing road locations & elevations, including temporary	Design calcs for cross sections and method of stabilization fo existing and planned channels (include temporary linings). Include appropriate permissible velocity and/or shear stress data.
access roads Lot and/or building numbers	Design calcs and construction details for energy dissipaters below culvert and storm sewer outlets (include stone/material specs &
Hydrogeologic features: rock outcrops, seeps, springs, wetland and their limits, streams, lakes, ponds, dams, etc. (include all required local or state buffer zones and any DWQ Riparian Buffer	apron dimensions). Avoid discharges on fill slopes Design calcs and dimension of sediment basins (note curren
determinations) Easements and drainageways, particularly required for offsite affected areas. Include copies of any recorded easements and/or	surface area and dewatering standards as well as diversion or runoff to the basins). Be sure that all surface drains, including ditches and berms, will have positive drainage to the basins.
agreements with adjoining property owners. Profiles of streets, utilities, ditch lines, etc.	VEGETATIVE STABILIZATION
Stockpiled topsoil or subsoil locations If the same person conducts the land-disturbing activity & any	Area & acreage to be stabilized with vegetation Method of soil preparation
related borrow or waste activity, the related borrow or waste activity shall constitute part of the land-disturbing activity unless the borrow	Seed type & rates (temporary & permanent) Fertilizer type and rates
or waste activity is regulated under the Mining Act of 1971, or is a landfill regulated by the Division of Waste Management. If the land-disturbing activity and any related borrow or waste activity are not	Mulch type and rates (include mulch anchoring methods) NOTE: Plan should include provisions for groundcover in accordance with NPDES Construction Stormwater General Permit NCG010000.
conducted by the same person, they shall be considered separate land-disturbing activities and must be permitted either through the	FINANCIAL RESPONSIBILITY/OWNERSHIP FORM
Sedimentation Pollution Control Act as a one-use borrow site or through the Mining Act.	Completed, signed & notarized FR/O Form
Location and details associated with any onsite stone crushing or other processing of material excavated. If the affected area	Accurate application fee payable to NCDEQ (\$100.00 per acre rounded up the next acre with no ceiling amount)
associated with excavation, processing, stockpiles and transport of such materials will comprise 1 or more acres, and materials will be	Certificate of assumed name, if the owner is a partnership Name of Registered Agent (if applicable)
leaving the development tract, a mining permit will be required. Required Army Corps 404 permit and Water Quality 401	Copy of the most current Deed for the site. Please make sure the deed(s) and ownership information are consistent between the plan sheets, local records and this form.
certification (e.g. stream disturbances over 150 linear feet) EROSION & SEDIMENT CONTROL MEASURES (on plan)	Provide latitude & longitude (in decimal degrees) at the project entrance.
Legend (provide appropriate symbols for all measures and	Two hard-copies of the plans (some regional offices require additional plans or multiple sizes; please contact the regional
reference them to the construction details) Location of temporary measures	coordinator prior to such submittal.) NOTE: For the Express Permitting Option, inquire at the local Regiona
Location of permanent measures Construction drawings and details for temporary and permanent	Office for availability. Express Reviews are performed by appointment only.
measures. Show measures to scale on plan and include proposed contours where necessary. Ensure design storage requirements	NARRATIVE AND CONSTRUCTION SEQUENCE
are maintained through all phases of construction. Maintenance requirements for measures Contact person responsible for maintenance	Narrative describing the nature & purpose of the construction activity.
SITE DRAINAGE FEATURES	Pre-construction conference, if requested. Construction sequence related to erosion and sediment control
Existing and planned drainage patterns (include off-site areas that	(including installation of critical measures prior to the initiation of the land-disturbing activity & removal of measures after areas the
drain through project and address temporary and permanent conveyance of stormwater over graded slopes)	serve are permanently stabilized). Address all phases of construction and necessary practices associated with temporary
Method used to determine acreage of land being disturbed and drainage areas to all proposed measures (e.g. delineation map)	stream bypasses and/or crossings Bid specifications related only to erosion control
Size, pipe material and location of culverts and sewers Soil information: type, special characteristics Soil information below culvert storm outlets	rev. 5.2025
Con information below current storm outlets	