ROY COOPER Governor ELIZABETH S. BISER Secretary MICHAEL ABRACZINSKAS Director



### XX

Leda Ochoa Plant Manager 3480 Taylorsville Highway Statesville, North Carolina 28625

SUBJECT: Air Quality Permit No. 03700T24 Facility ID: 4900121 3A Composites USA Inc. Statesville, North Carolina Iredell County Fee Class: Title V PSD Class: Minor

#### Dear Ms. Ochoa:

In accordance with your completed Air Quality Permit Application for a renewal of your Title V permit, received on May 1, 2023, we are forwarding herewith Air Quality Permit No. 03700T24 authorizing the construction and operation, of the emission source(s) and associated air pollution control device(s) specified herein. Additionally, any emissions activities determined from your Air Quality Permit Application as being insignificant per 15A North Carolina Administrative Code 02Q .0503(8) have been identified as such in the permit. Please note the requirements for the annual compliance certification are contained in General Condition P in Section 4. The current owner is responsible for submitting a compliance certification for the entire year regardless of who owned the facility during the year.

As the designated responsible official, it is your responsibility to review, understand, and abide by all of the terms and conditions of the attached permit. It is also your responsibility to ensure that any person who operates any emission source and associated air pollution control device subject to any term or condition of the attached permit reviews, understands, and abides by the condition(s) of the attached permit that are applicable to that particular emission source.

If any parts, requirements, or limitations contained in this Air Quality Permit are unacceptable to you, you have the right to file a petition for contested case hearing in the North Carolina Office of Administrative Hearings. Information regarding the right, procedure, and time limit for permittees and other persons aggrieved to file such a petition is contained in the attached "Notice Regarding the Right to Contest A Division of Air Quality Permit Decision."

The construction of new air pollution emission source(s) and associated air pollution control device(s), or modifications to existing emission source(s) and air pollution control device(s) described in this permit must be covered under an Air Quality Permit issued by the Division of Air Quality prior to construction unless the Permittee has fulfilled the requirements of NCGS 143-215.108A(b) and received written approval from the Director of the Division of Air Quality to commence construction. Failure to receive an Air Quality Permit or written approval prior to commencing construction is a violation of NCGS



143-215.108A and may subject the Permittee to civil or criminal penalties as described in NCGS 143-215.114A and 143-215.114B.

Iredell County has triggered increment tracking under PSD for sulfur dioxide (SO<sub>2</sub>), nitrogen oxides ( $NO_x$ ), and  $PM_{10}$ . However, this permit renewal does not consume or expand increments for any pollutants.

This Air Quality Permit shall be effective from *(Enter Permit Issuance Date)* until *(Enter Permit Expiration Date)*, is nontransferable to future owners and operators, and shall be subject to the conditions and limitations as specified therein.

Should you have any questions concerning this matter, please contact Jacob Larson at (919) 707-8407 or Jacob.Larson@deq.nc.gov.

Sincerely yours,

Mark J. Cuilla, EIT, CPM, Chief, Permitting Section Division of Air Quality, NCDEQ

Enclosure

c: Brad Akers, EPA Region 4 (Permit and Review) Laserfiche (4900121)

#### NOTICE REGARDING THE RIGHT TO CONTEST A DIVISION OF AIR QUALITY PERMIT DECISION

**Right of the Permit Applicant or Permittee to File a Contested Case:** Pursuant to NCGS 143-215.108(e), a permit applicant or permittee who is dissatisfied with the Division of Air Quality's decision on a permit application may commence a contested case by filing a petition under NCGS 150B-23 in the Office of Administrative Hearings within 30 days after the Division notifies the applicant or permittee does not file a petition within the required time, the Division's decision on the application is final and is not subject to review. The filing of a petition will stay the Division's decision until resolution of the contested case.

**Right of Other Persons Aggrieved to File a Contested Case:** Pursuant to NCGS 143-215.108(e1), a person other than an applicant or permittee who is a person aggrieved by the Division's decision on a permit application may commence a contested case by filing a petition under NCGS 150B-23 within 30 days after the Division provides notice of its decision on a permit application, as provided in NCGS 150B-23(f), or by posting the decision on a publicly available Web site. The filing of a petition under this subsection does not stay the Division's decision except as ordered by the administrative law judge under NCGS 150B-33(b).

**General Filing Instructions:** A petition for contested case hearing must be in the form of a written petition, conforming to NCGS 150B-23, and filed with the Office of Administrative Hearings, 1711 New Hope Church Road, Raleigh NC, 27609, along with a fee in an amount provided in NCGS 150B-23.2. A petition for contested case hearing form may be obtained upon request from the Office of Administrative Hearings or on its website at https://www.oah.nc.gov/hearings-division/filing/hearing-forms. Additional specific instructions for filing a petition are set forth at 26 NCAC Chapter 03.

**Service Instructions:** A party filing a contested case is required to serve a copy of the petition, by any means authorized under 26 NCAC 03 .0102, on the process agent for the Department of Environmental Quality:

William F. Lane, General Counsel North Carolina Department of Environmental Quality 1601 Mail Service Center Raleigh, North Carolina 27699-1601

If the party filing the petition is a person aggrieved other than the permittee or permit applicant, the party **must also** serve the permittee in accordance with NCGS 150B-23(a).

\* \* \*

Additional information is available at <u>https://www.oah.nc.gov/hearings-division/hearing-process/filing-contested-case</u>. Please contact the OAH at 984-236-1850 or oah.postmaster@oah.nc.gov with all questions regarding the filing fee and/or the details of the filing process.

## Summary of Changes to Permit

Page No.	Section	Description of Changes
	Cover page and throughout permit	• Updated all dates and permit revision numbers.
3	Cover page	Added "Notice Regarding The Right To Contest A Division Of Air Quality Permit Decision" page
4	Summary of Changes to Permit	<ul> <li>Added summary of changes made to Permit No. 03700T23 according to the most recent requirements of the renewal Title V permit</li> </ul>
2	Table of Contents	<ul> <li>Added Section 3.0 as "Insignificant Activities List"</li> <li>Added Section 4.0 as "General Permit Conditions"</li> </ul>
3	List of Acronyms	Added "List of Acronyms"
4	Permitted emissions table	<ul> <li>Rearranged sources to follow the order of the permit</li> <li>Removed ES-4 and ES-8</li> </ul>
5	2.1 A.1.a	Updated monitoring condition to current requirement
6	2.1 A.3.c	• Updated monitoring condition to be consistent with shell language
8	2.1 C.1.a	Updated condition to be consistent with shell language
8	2.1 C.1.c	• Updated monitoring condition to be consistent with shell language
10	2.1 D.1.c	• Updated monitoring condition to be consistent with shell language
11	2.1 D.2.c	• Updated monitoring condition to be consistent with shell language
12	2.1 E.	<ul> <li>Removed 112(j) condition from permit</li> <li>Removed applicability date for MACT DDDDD from table</li> </ul>
12	2.1 E.1	Updated condition to be consistent with current shell language
13	2.1 E.4	<ul> <li>Updated MACT DDDDD condition to current regulatory requirements</li> <li>Removed 112(j) condition.</li> <li>Changed numbering</li> </ul>
17	2.2 A.1	Updated MACT JJJJ to current regulatory requirements
20	2.2 B.1	• Updated condition and table to be consistent with shell format
22	2.2 C.1	• Updated condition and table to be consistent with shell format
22	2.2 C.2	Added odorous emissions condition to permit
23	Section 3	<ul> <li>Added Insignificant Activities as Section 3 of the Title V Permit</li> <li>Added IES-4 and IES-8 to Insignificant Activities</li> </ul>
24	Section 4	<ul> <li>Added General Conditions as Section 4 of the Title V Permit</li> <li>Updated General Conditions to version 7.0, 08/21/2023</li> </ul>

The following changes were made to Air Permit No. 03700T23:\*

\* This list is not intended to be a detailed record of every change made to the permit but a summary of those changes.



## State of North Carolina Department of Environmental Quality Division of Air Quality

# AIR QUALITY PERMIT

Permit No.	Replaces Permit No.	Effective Date	Expiration Date
03700T24	03700T23	XXXX*	XXXX**

NOTE: Per General Condition K, a permit application for the renewal of this Title V permit shall be submitted no later than *[enter date six months prior to expiration date]*.

Until such time as this permit expires or is modified or revoked, the below named Permittee is permitted to construct and operate the emission source(s) and associated air pollution control device(s) specified herein, in accordance with the terms, conditions, and limitations within this permit. This permit is issued under the provisions of Article 21B of Chapter 143, General Statutes of North Carolina as amended, and Title 15A North Carolina Administrative Codes (15A NCAC), Subchapters 02D and 02Q, and other applicable Laws.

Pursuant to Title 15A NCAC, Subchapter 02Q, the Permittee shall not construct, operate, or modify any emission source(s) or air pollution control device(s) without having first submitted a complete Air Quality Permit Application to the permitting authority and received an Air Quality Permit, except as provided in this permit.

Permittee:	<b>3A Composites USA Inc.</b>
Facility ID:	4900121
Primary SIC Code:	2672
NAICS Code:	322222
Facility Site Location:	3480 Taylorsville Highway
City, County, State, Zip:	Statesville, Iredell County, North Carolina 28687
Mailing Address:	3480 Taylorsville Highway
City, State, Zip:	Statesville, North Carolina 28687
Application Number(s):	4900121.23A
Complete Application Date(s):	May 1, 2023
Division of Air Quality,	Mooresville Regional Office
<b>Regional Office Address:</b>	610 East Center Avenue, Suite 301
C	Mooresville, North Carolina 28115

Permit issued this the XX day of XXXXX, 2024.

Mark J. Cuilla, EIT, CPM, Chief, Air Permitting Section By Authority of the Environmental Management Commission

#### Table of Contents

#### LIST OF ACRONYMS

- SECTION 1: PERMITTED EMISSION SOURCE(S) AND ASSOCIATED AIR POLLUTION CONTROL DEVICE(S) AND APPURTENANCES
- SECTION 2: SPECIFIC LIMITATIONS AND CONDITIONS
  - 2.1 Emission Source(s) Specific Limitations and Conditions (Including specific requirements, testing, monitoring, recordkeeping, and reporting requirements)
  - 2.2 Multiple Emission Source(s) Specific Limitations and Conditions (Including specific requirements, testing, monitoring, recordkeeping, and reporting requirements)
- SECTION 3: INSIGNIFICANT ACTIVITIES PER 15A NCAC 02Q .0503(8)
- SECTION 4: GENERAL PERMIT CONDITIONS

#### List of Acronyms

AOS	Alternative Operating Scenario
BACT	Best Available Control Technology
BAE	Baseline Actual Emissions
Btu	British thermal unit
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CEDRI	Compliance and Emissions Data Reporting Interface
CFR	Code of Federal Regulations
CO	Carbon Monoxide
COMS	Continuous Opacity Monitoring System
CSAPR	Cross-State Air Pollution Rule
DAQ	Division of Air Quality
DEQ	Department of Environmental Quality
EMC EPA	Environmental Management Commission
FR	Environmental Protection Agency Federal Register
GACT	Generally Available Control Technology
GHGs	Greenhouse Gases
НАР	Hazardous Air Pollutant
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
NAA	Non-Attainment Area
NAAQS	National Ambient Air Quality Standards
NAICS	North American Industry Classification System
NCAC	North Carolina Administrative Code
NCGS	North Carolina General Statutes
NESHAP	National Emission Standards for Hazardous Air Pollutants
NOx	Nitrogen Oxides
NSPS	New Source Performance Standard
NSR	New Source Review
OAH DAE	Office of Administrative Hearings
PAE PAL	Projected Actual Emissions Plantwide Applicability Limitation
PM	Particulate Matter
PM2.5	Particulate Matter with Nominal Aerodynamic Diameter of 2.5 Micrometers or Less
$PM_{10}$	Particulate Matter with Nominal Aerodynamic Diameter of 10 Micrometers of Less
POS	Primary Operating Scenario
PSD	Prevention of Significant Deterioration
РТЕ	Potential to Emit
RACT	Reasonably Available Control Technology
SIC	Standard Industrial Classification
SIP	State Implementation Plan
SO <sub>2</sub>	Sulfur Dioxide
ТАР	Toxic Air Pollutant
tpy	Tons Per Year
VOC	Volatile Organic Compound

### SECTION 1- PERMITTED EMISSION SOURCE(S) AND ASSOCIATED AIR POLLUTION CONTROL DEVICE(S) AND APPURTENANCES

The following table contains a summary of all permitted emission sources and associated air pollution control devices and appurtenances:

Emission Source ID No.	Emission Source Description	Control Device	Control Device Description
ES-1	Saturator operation including two (2) natural gas/propane-fired	ID No. N/A	N/A
	saturator dryers (24.0 million Btu per hour combined maximum heat input)		
ES-17, ES-18, and ES-19	Three (3) mixing tanks (two at 1,274 gallons and one at 300 gallons)		
MACT JJJJ			
ES-3505 ES-3503 ES-3516 ES-3502	Pre-press operation including: One No. 2 15-open pre-press One No. 1 15-open pre-press One 9-open pre-press One 10-open pre-press	N/A	N/A
ES-29	Heavy Duty Graphics Arts Foam Board Process consisting of glue mixing, lift tables, roll coater, conveying, and cold press pods	N/A	N/A
	Gatorfoam production operation including:	N/A	N/A
ES-22	Two (2) glue spreader presslines		
ES-27	Sanding operation including one 5 foot by 10 foot Hesseman caul plate sander	CD-168	Fabric filter (1,390 square feet of filter area)
ES-30	Foam/paperboard finishing equipment	CD-30	Dust collector (2,617 square feet of filter area)
ES-7 MACT DDDDD	Natural gas/propane-fired boiler (25.1 million Btu per hour heat input)	N/A	N/A
ES-31 MACT JJJJ	Lamination Line	NA	NA

## **SECTION 2 - SPECIFIC LIMITATIONS AND CONDITIONS**

# 2.1 Emission Source(s) and Control Devices(s) Specific Limitations and Conditions

The emission source(s) and associated air pollution control device(s) and appurtenances listed below are subject to the following specific terms, conditions, and limitations, including the testing, monitoring, recordkeeping, and reporting requirements as specified herein:

## A. Saturator operation consisting of two (2) natural gas/propane-fired saturator dryers (ID No. ES-1) and three (3) mixing tanks (ID Nos. ES-17, ES-18 and ES-19)

Pollutant	Limits/Standards	Applicable Regulation
Particulate matter	$E = 4.10 * P^{0.67}$	15A NCAC 02D .0515
	Where, E is the allowable emission rate (pounds per hour)	
	P is the process input weight (tons per hour)	
Sulfur dioxide	ID No. ES-1	15A NCAC 02D .0516
	2.3 pounds per million Btu heat input	
Visible emissions	ID Nos. ES-17, ES-18, and ES-19	15A NCAC 02D .0521
	40 percent opacity	
	ID No. ES-1 20 percent opacity	
Hazardous air	See Section 2.2 A	15A NCAC 02D .1111
pollutants		40 CFR 63, Subpart JJJJ
Toxic air pollutants	State-enforceable only	15A NCAC 02D .1100
	See Section 2.2 B	

The following table provides a summary of limits and standards for the emission source(s) described above:

#### 1. 15A NCAC 02D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

a. Emissions of particulate matter from these sources (**ID Nos. ES-1, ES-17, ES-18, and ES-19**) shall not exceed an allowable emission rate as calculated by the following equation:

$E = 4.10 \text{ x } P^{0.67}$	(for process rates less than or equal to 30 tons per hour), or
$E = 55.0 \text{ x } P^{0.11} - 40$	(for process rates greater than 30 tons per hour)

Where E = allowable emission rate in pounds per hour P = process weight in tons per hour

Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

#### Testing [15A NCAC 02Q .0508(f)]

b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 A.1.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .0515.

#### Monitoring/Recordkeeping/Reporting [15A NCAC 02Q .0508(f)]

- c. The Permittee shall maintain production records such that the process rates "P" in tons per hour, as specified by the formulas contained above, can be derived and shall make these records available to a DAQ authorized representative upon request. The Permittee shall be deemed in noncompliance with 15A NCAC 02D .0515 if the production records are not maintained or the types of materials and finishes are not monitored.
- d. No reporting is required for particulate emissions from these sources (ID Nos. ES-1, ES-17, ES-18, and ES-19).

#### 2. 15A NCAC 02D .0516: SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

a. Emissions of sulfur dioxide from this source (**ID No. ES-1**) shall not exceed 2.3 pounds per million Btu heat input. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard.

#### Testing [15A NCAC 02Q .0508(f)]

b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 A.2.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .0516.

#### Monitoring/Recordkeeping [15A NCAC 02Q .0508(f)]

c. No monitoring/recordkeeping/reporting is required for sulfur dioxide emissions from the firing of natural gas or propane in this source (**ID No. ES-1**).

#### 3. 15A NCAC 02D .0521: CONTROL OF VISIBLE EMISSIONS

- a. Visible emissions from the mix tanks (ID Nos. ES-17, ES-18, and ES-19) shall not be more than 40 percent opacity when averaged over a six-minute period. However, six-minute averaging periods may exceed 40 percent not more than once in any hour and not more than four times in any 24-hour period. In no event shall the six-minute average exceed 90 percent opacity.
- b. Visible emissions from the natural gas/propane-fired saturator dryers (**ID No. ES-1**) shall not be more than 20 percent opacity when averaged over a six-minute period. However, six-minute averaging periods may exceed 20 percent not more than once in any hour and not more than four times in any 24-hour period. In no event shall the six-minute average exceed 87 percent opacity.

#### Testing [15A NCAC 02Q .0508(f)]

c. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limits given in Sections 2.1 A.3.a and b above, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .0521.

#### Monitoring [15A NCAC 02Q .0508(f)]

- d. To ensure compliance, once a month the Permittee shall observe the emission points of these sources (ID Nos. ID Nos. ES-1, ES-17, ES-18, and ES-19) for any visible emissions above normal. The monthly observation must be made for each month of the calendar year period to ensure compliance with this requirement. If visible emissions from these sources are observed to be above normal, the Permittee shall either:
  - i. take appropriate action to correct the above-normal emissions as soon as practicable and within the monitoring period and record the action taken as provided in the recordkeeping requirements below, or
  - ii. demonstrate that the percent opacity from the emission points of the emission source in accordance with 15A NCAC 02D .2610 (Method 9) for 12 minutes is below the limit given in Section 2.1 A.3.a or b above.

The Permittee shall be deemed to be in noncompliance with 15A NCAC 02D .0521 if the required monthly observations are not conducted as required; if the above-normal emissions are not corrected within the monitoring period or the percent opacity demonstration cannot be made.

#### Recordkeeping [15A NCAC 02Q .0508(f)]

- e. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
  - i. the date and time of each recorded action;
  - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
  - iii. the results of any corrective actions performed.

The Permittee shall be deemed in noncompliance with 15A NCAC 02D .0521 if these records are not maintained.

#### Reporting [15A NCAC 02Q .0508(f)]

f. The Permittee shall submit a summary report of the monitoring and recordkeeping activities given in Section(s) 2.1 A.3.d and e above postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified. B. Pre-press operation including one No. 2 15-open pre-press (ID No. ES-3505), one No. 1 15-open pre-press (ID No. ES-3503), one 9-open pre-press (ID No. ES-3516), and one (1) 10-open pre-press (ID No. ES-3502).

One Heavy Duty Graphics Arts Foam Board Process consisting of glue mixing, lift tables, roll coater, conveying, and cold press pods (ID No. ES-29)

The following table provides a summary of limits and standards for the emission source(s) described above:

Pollutant	Limits/Standards	Applicable Regulation
Toxic air pollutants	State-enforceable only See Section 2.2 B	15A NCAC 02D .1100

#### C. Gatorfoam Production Operation including two glue spreader presslines (ID No. ES-22)

Pollutant	Limits/Standards	Applicable Regulation
Particulate matter including PM <sub>10</sub>	$E = 4.10*P^{0.67}$ Where, E is the allowable emission rate (pounds per hour) P is the process weight rate (tons per hour)	15A NCAC 02D .0515
Visible emissions	40 percent opacity	15A NCAC 02D .0521
Toxic air pollutants	State-enforceable only See Section 2.2 B	15A NCAC 02D .1100

The following table provides a summary of limits and standards for the emission source(s) described above:

#### 1. 15A NCAC 02D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

a. Emissions of particulate matter from this source (ID Nos. ES-22) shall not exceed an allowable emission rate as calculated by the following equation:

$E = 4.10 \text{ x } P^{0.67}$	(for process rates less than or equal to 30 tons per hour), or
$E = 55.0 \text{ x } P^{0.11} - 40$	(for process rates greater than 30 tons per hour)

Where E = allowable emission rate in pounds per hour P = process weight in tons per hour

Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

#### Testing [15A NCAC 02Q .0508(f)]

b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 C.1.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .0515.

#### Monitoring/Record keeping/Reporting [15A NCAC 02Q .0508(f)]

- c. The Permittee shall maintain production records such that the process rates "P" in tons per hour, as specified by the formulas contained above can be derived, and shall make these records available to a DAQ authorized representative upon request. The Permittee shall be deemed in noncompliance with 15A NCAC 02D .0515 if the production records are not maintained or the types of materials and finishes are not monitored.
- d. No reporting is required for particulate emissions from this source (ID Nos. ES-22).

#### 2. 15A NCAC 02D .0521: CONTROL OF VISIBLE EMISSIONS

a. Visible emissions from the gatorfoam production operation (**ID No. ES-22**) shall not be more than 40 percent opacity when averaged over a six-minute period. However, six-minute averaging periods may exceed 40 percent not more than once in any hour and not more than four times in any 24-hour period. In no event shall the six-minute average exceed 90 percent opacity.

#### Testing [15A NCAC 02Q .0508(f)]

b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 C.2.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .0521.

#### Monitoring [15A NCAC 02Q .0508(f)]

c. To ensure compliance, once a month the Permittee shall observe the emission points of this sources (ID Nos. ES-22) for any visible emissions above normal. The monthly observation must be made for each month of the calendar year period to ensure compliance with this requirement. If visible emissions from this observed to be above normal, the Permittee shall either:

- i. take appropriate action to correct the above-normal emissions as soon as practicable and within the monitoring period and record the action taken as provided in the recordkeeping requirements below, or
- ii. demonstrate that the percent opacity from the emission points of the emission source in accordance with 15A NCAC 02D .2610 (Method 9) for 12 minutes is below the limit given in Section 2.1 C.2.a above.

The Permittee shall be deemed to be in noncompliance with 15A NCAC 02D .0521 if the required monthly observations are not conducted as required; if the above-normal emissions are not corrected within the monitoring period or the percent opacity demonstration cannot be made.

#### Recordkeeping [15A NCAC 02Q .0508(f)]

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
  - i. the date and time of each recorded action;
  - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
  - iii. the results of any corrective actions performed.

The Permittee shall be deemed in noncompliance with 15A NCAC 02D .0521 if these records are not maintained.

#### Reporting [15A NCAC 02Q .0508(f)]

e. The Permittee shall submit a summary report of the monitoring and recordkeeping activities given in Section(s) 2.1 C.2.c and d above postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

## D. Sanding operation including one 5x10 Hesseman caul plate sander (ID No. ES-27) with associated bagfilter (ID No. CD-168)

## Foam/paperboard finishing equipment (ID No. ES-30) with associated dust collection (ID No. CD-30)

The following table provides a summary of limits and standards for the emission source(s) described above:

Pollutant	Limits/Standards	Applicable Regulation
Particulate matter	$E = 4.10 * P^{0.67}$	15A NCAC 02D .0515
including PM <sub>10</sub>	Where, E is the allowable emission rate (pounds per hour)	
	P is the process weight rate (tons per hour)	
Visible emissions	20 percent opacity	15A NCAC 02D .0521

#### 1. 15A NCAC 02D .0515: PARTICULATES FROM MISCELLANEOUS INDUSTRIAL PROCESSES

a. Emissions of particulate matter from these sources (ID Nos. ES-27 and ES-30) shall not exceed an allowable emission rate as calculated by the following equation:

$E = 4.10 \text{ x } P^{0.67}$	(for process rates less than or equal to 30 tons per hour), or
$E = 55.0 \text{ x } P^{0.11} - 40$	(for process rates greater than 30 tons per hour)

Where E = allowable emission rate in pounds per hour P = process weight in tons per hour

Liquid and gaseous fuels and combustion air are not considered as part of the process weight.

#### Testing [15A NCAC 02Q .0508(f)]

b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 D.1.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .0515.

#### Monitoring [15A NCAC 02Q .0508(f)]

- c. Particulate matter emissions from this/these sources (ID Nos. ES-27 and ES-30) shall be controlled by the bagfilter and dust collector (ID Nos. CD-168 and CD-30). To ensure compliance, the Permittee shall perform inspections and maintenance as recommended by the manufacturer. In addition to the manufacturer's inspection and maintenance recommendations, or if there are no manufacturer's inspection and maintenance recommendations, as a minimum, the inspection and maintenance requirement shall include the following:
  - i. a monthly visual inspection of the system ductwork and material collection unit for leaks; and
  - ii. an annual (for each 12-month period following the initial inspection) internal inspection of the bagfilter's structural integrity.

The Permittee shall be deemed in noncompliance with 15A NCAC 02D .0515 if the ductwork and bagfilters are not inspected and maintained.

#### Recordkeeping [15A NCAC 02Q .0508(f)]

- d. The results of inspection and maintenance shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
  - i. the date and time of each recorded action;
  - ii. the results of each inspection;
  - iii. the results of any maintenance performed on any control device; and
  - iv. any variance from manufacturer's recommendations, if any, and corrections made.

The Permittee shall be deemed in noncompliance with 15A NCAC 02D .0515 if these records are not maintained.

#### Reporting [15A NCAC 02Q .0508(f)]

e. The Permittee shall submit the results of any maintenance performed on the bagfilter (ID No. CD-168) or dust collector (ID No. CD-30) within 30 days of a written request by the DAQ.

Permit 03700T24 Page 11

f. The Permittee shall submit a summary report of monitoring and recordkeeping activities given in Sections 2.1 D.1.c and d above postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

#### 2. 15A NCAC 02D .0521: CONTROL OF VISIBLE EMISSIONS

a. Visible emissions from the sanding operation (ID Nos. ES-27) and the foam/paperboard finishing equipment (ID No. ES-30) shall not be more than 20 percent opacity when averaged over a six-minute period. However, six-minute averaging periods may exceed 20 percent not more than once in any hour and not more than four times in any 24-hour period. In no event shall the six-minute average exceed 87 percent opacity.

#### Testing [15A NCAC 02Q .0508(f)]

b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 D.2.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .0521.

#### Monitoring [15A NCAC 02Q .0508(f)]

- c. To ensure compliance, once a month the Permittee shall observe the emission points of these sources (ID Nos. ES-27 and ES-30) for any visible emissions above normal. The monthly observation must be made for each month of the calendar year period to ensure compliance with this requirement. If visible emissions from these sources are observed to be above normal, the Permittee shall either:
  - i. take appropriate action to correct the above-normal emissions as soon as practicable and within the monitoring period and record the action taken as provided in the recordkeeping requirements below, or
  - ii. demonstrate that the percent opacity from the emission points of the emission source in accordance with 15A NCAC 02D .2610 (Method 9) for 12 minutes is below the limit given in Section 2.1 D.2.a above.

The Permittee shall be deemed to be in noncompliance with 15A NCAC 02D .0521 if the required monthly observations are not conducted as required; if the above-normal emissions are not corrected within the monitoring period or the percent opacity demonstration cannot be made.

#### Recordkeeping [15A NCAC 02Q .0508(f)]

- d. The results of the monitoring shall be maintained in a logbook (written or electronic format) on-site and made available to an authorized representative upon request. The logbook shall record the following:
  - i. the date and time of each recorded action;
  - ii. the results of each observation and/or test noting those sources with emissions that were observed to be in noncompliance along with any corrective actions taken to reduce visible emissions; and
  - iii. the results of any corrective actions performed.

The Permittee shall be deemed in noncompliance with 15A NCAC 02D .0521 if these records are not maintained.

#### Reporting [15A NCAC 02Q .0508(f)]

e. The Permittee shall submit a summary report of the monitoring and recordkeeping activities given in Section(s) 2.1 D.2.c and d above postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December and July 30 of each calendar year for the preceding six-month period between January and June. All instances of deviations from the requirements of this permit must be clearly identified.

#### E. Natural gas/propane-fired boiler (ID No. ES-7)

Pollutant	Limits/Standards	Applicable Regulation
Particulate matter including PM10	0.472 pounds per million Btu heat input	15A NCAC 02D .0503
Sulfur dioxide	2.3 pounds per million Btu heat input	15A NCAC 02D .0516
Visible emissions	40 percent opacity	15A NCAC 02D .0521
HAPs	Existing Gas 1 unit greater than 10 million Btu per hour	15A NCAC 02D .1111 40 CFR 63 Subpart DDDDD

The following table provides a summary of limits and standards for the emission source(s) described above:

#### 1. 15A NCAC 02D .0503: PARTICULATES FROM FUEL BURNING INDIRECT HEAT EXCHANGERS

a. Emissions of particulate matter from the combustion of natural gas or propane, that are discharged from this source (**ID. No. ES-7**) into the atmosphere shall not exceed **0.472** pounds per million Btu heat input.

#### Testing [15A NCAC 02Q .0508(f)]

b. If emissions testing is required, the testing shall be performed in accordance General Condition JJ. If the results of this test are above the limit given in Section 2.1 E.1.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .0503.

#### Monitoring/Record keeping/Reporting [15A NCAC 02Q .0508(f)]

c. No monitoring/recordkeeping/reporting is required for particulate emissions from the firing of natural gas or propane in this source (ID No. ES-7).

#### 2. 15A NCAC 02D .0516: SULFUR DIOXIDE EMISSIONS FROM COMBUSTION SOURCES

a. Emissions of sulfur dioxide from this source (**ID No. ES-7**) shall not exceed 2.3 pounds per million Btu heat input. Sulfur dioxide formed by the combustion of sulfur in fuels, wastes, ores, and other substances shall be included when determining compliance with this standard.

#### Testing [15A NCAC 02Q .0508(f)]

b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 E.2.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .0516.

#### Monitoring/Recordkeeping [15A NCAC 02Q .0508(f)]

c. No monitoring/recordkeeping is required for sulfur dioxide emissions from the firing of natural gas or propane in this boiler (ID No. ES-7).

#### 3. 15A NCAC 02D .0521: CONTROL OF VISIBLE EMISSIONS

a. Visible emissions from this boiler (ID No. ES-7) shall not be more than 40 percent opacity when averaged over a six-minute period. However, six-minute averaging periods may exceed 40 percent not more than once in any hour and not more than four times in any 24-hour period. In no event shall the six-minute average exceed 90 percent opacity.

#### Testing [15A NCAC 02Q .0508(f)]

b. If emissions testing is required, the testing shall be performed in accordance with General Condition JJ. If the results of this test are above the limit given in Section 2.1 E.3.a above, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .0521.

#### Monitoring/Recordkeeping/Reporting [15A NCAC 02Q .0508(f)]

c. No monitoring/recordkeeping/reporting is required for visible emissions from the firing of natural gas or propane in

this boiler.

#### 4. 15A NCAC 02D .1111: MAXIMUM ACHIEVABLE CONTROL TECHNOLOGY

#### Applicability [40 CFR 63.7485, 63.7490(d), 63.7499(l)]

a. For these sources (ID Nos. ES-7) (existing sources(s) designed to burn gas 1 fuels with a heat input capacity equal to or greater than 10 million Btu per hour with no oxygen trim), the Permittee shall comply with all applicable provisions, including the monitoring, recordkeeping, and reporting contained in Environmental Management Commission Standard 15A NCAC 02D .1111 "Maximum Achievable Control Technology" (MACT) as promulgated in 40 CFR 63 Subpart DDDDD "National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters" including Subpart A "General Provisions."

#### **Definitions and Nomenclature**

b. For the purpose of this permit condition, the definitions and nomenclature contained in 40 CFR 63.7575 shall apply. [40 CFR 63.7575]

#### 40 CFR Part 63 Subpart A General Provisions

c. The Permittee shall comply with the requirements of 40 CFR 63 Subpart A General Provisions according to the applicability of Subpart A to such sources as identified in Table 10 to 40 CFR Part 63 Subpart DDDDD. [40 CFR 63.7565]

#### Compliance Date

d. The Permittee shall complete the initial tune up and the one-time energy assessment no later than May 20, 2019. [40 CFR 63. 7510(e), 63.56(b)] *These requirements have been met.* 

#### **Notifications**

e. The Permittee shall submit a Notification of Compliance Status. The notification shall be signed by a responsible official and submitted by July 19, 2019.[40 CFR 63.7545(e), 63.7530(e)] *This requirement has been met.* 

#### Work Practice Standards [15A NCAC 02Q .0508(b)]

- f. The following work practice standards apply:
  - i. The Permittee shall conduct a tune-up of the boiler annually while burning the type of fuel (or fuels in case of units that routinely burn a mixture) that provided the majority of the heat input to the boiler or process heater over the 12 months prior to the tune-up as specified below:
    - (A) As applicable, inspect the burner, and clean or replace any components of the burner as necessary (the Permittee may perform the burner inspection any time prior to the tune-up or delay the burner inspection until the next scheduled unit shutdown;
    - (B) Inspect the flame pattern, as applicable, and adjust the burner as necessary to optimize the flame pattern. The adjustment should be consistent with the manufacturer's specifications, if available;
    - (C) Inspect the system controlling the air-to-fuel ratio, as applicable, and ensure that it is correctly calibrated and functioning properly (the Permittee may delay the inspection until the next scheduled unit shutdown);
    - (D) Optimize total emissions of carbon monoxide. This optimization should be consistent with the manufacturer's specifications, if available, and with any NO<sub>X</sub> requirement to which the unit is subject; and
    - (E) Measure the concentrations in the effluent stream of carbon monoxide in parts per million, by volume, and oxygen in volume percent, before and after the adjustments are made (measurements may be either on a dry or wet basis, as long as it is the same basis before and after the adjustments are made). Measurements may be taken using a portable CO analyzer.

[40 CFR 63.7500(a) and (e), 63.7540(a)(10)]

- ii. Each annual tune-up shall be conducted no more than 13 months after the previous tune-up. [40 CFR 63.7515(d)]
- iii. If the unit is not operating on the required date for a tune-up, the tune-up shall be conducted within 30 calendar days of startup. [40 CFR 63.7540(a)(13), 63.7515(g)]
- iv. At all times, the Permittee shall operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator that may include, but is not limited to,

monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source. [40 CFR 63.7500(a)(3)]

The Permittee shall be deemed in noncompliance with 15A NCAC 02D .1111 if these work practice requirements are not met.

#### Energy Assessment Requirements [15A NCAC 02Q .0508(b)]

g. The Permittee shall have a one-time energy assessment performed by a qualified energy assessor. [40 CFR 63.7500(a)(1), Table 3 to 40 CFR Subpart DDDDDD] *This requirement has been met.* 

#### Recordkeeping Requirements [15A NCAC 02Q .0508(f), 40 CFR 63.7555]

- h. The following recordkeeping requirements apply:
  - i. keep a copy of each notification and report submitted to comply with this subpart, including all documentation supporting any Initial Notification or Notification of Compliance Status, or semiannual compliance report that has been submitted, according to the requirements in 40 CFR 63.10(b)(2)(xiv). [40 CFR 63.7555(a)(1)]
  - ii. maintain on-site and submit, if requested by the Administrator, an annual report containing the information in paragraphs (A) through (C) below:
    - (A) the concentrations of carbon monoxide in the effluent stream in parts per million by volume, and oxygen in volume percent, measured at high fire or typical operating load, before and after the tune-up of the source;
    - (B) a description of any corrective actions taken as a part of the tune-up; and
    - (C) the type and amount of fuel used over the 12 months prior to the tune-up, but only if the unit was physically and legally capable of using more than one type of fuel during that period. Units sharing a fuel meter may estimate the fuel use by each unit.
    - [40 CFR 63.7540(a)(10)(vi)]
  - iii. keep the associated records for Sections 2.1 E.4.f through g.
  - iv. keep:
    - (A) records in a form suitable and readily available for expeditious review;
    - (B) each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record; and
    - (C) each record on site for at least 2 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record. The Permittee can keep the records offsite for the remaining 3 years.
    - [40 CFR 63.7560, 63.10(b)(1)]

The Permittee shall be deemed in noncompliance with 15A NCAC 02D .1111 if these recordkeeping requirements are not met.

#### Reporting Requirements [15A NCAC 02Q .0508(f)]

- i. The following reporting requirements apply:
  - i. The Permittee shall submit compliance reports to the DAQ on an annual basis. Annual reports shall cover the periods from January 1 to December 31. The Permittee shall submit the compliance report postmarked on or before January 30 for the preceding reporting period. [40 CFR 63.7550(a) and (b)]
  - ii. This report shall also be submitted electronically via the Compliance and Emissions Data Reporting Interface (CEDRI). (CEDRI can be accessed through the EPA's Central Data Exchange (CDX) (https://cdx.epa.gov/).) The Permittee shall use the appropriate electronic report in CEDRI for this subpart. Instead of using the electronic report in CEDRI for this subpart, the Permittee shall submit an alternate electronic file consistent with the XML schema listed on the CEDRI Web site (http://www.epa.gov/ttn/chief/cedri/index.html), once the XML schema is available. If the reporting form specific to this subpart is not available in CEDRI at the time that the report is due, the Permittee shall submit the report to the Administrator at the appropriate address listed in 40 CFR 63.13. The Permittee shall begin submitting reports via CEDRI no later than 90 days after the form becomes available in CEDRI. [40 CFR 63.7550(h)(3)]
  - iii. The compliance report shall contain the following information:
    - (A) company name and address;
    - (B) process unit information, emissions limitations, and operating parameter limitations;
    - (C) date of report and beginning and ending dates of the reporting period;
    - (D) date of the most recent tune-up for each unit required according to Section 2.1 E.4.f. Include the date of the most recent burner inspection; and
    - (E) statement by a responsible official with that official's name, title, and signature, certifying the truth, accuracy, and completeness of the content of the report.
    - [40 CFR 63.7550(a) and (c), Table 9 to Subpart DDDDD]

The Permittee shall be deemed in noncompliance with 15A NCAC 02D .1111 if these reporting requirements are not met.

#### F. Lamination Line (ID No. ES-31)

The following table provides a summary of limits and standards for the emission source(s) described above:

Pollutant	Limits/Standards	Applicable Regulation
Hazardous air	See Section 2.2 A	15A NCAC 02D .1111
pollutants		40 CFR 63, Subpart JJJJ

### 2.2 Multiple Emission Source(s) Specific Limitations and Conditions

#### A. Saturator Operation and Lamination Line:

Two (2) natural gas/propane-fired saturator dryers (ID No. ES-1) Three (3) mixing tanks (ID Nos. ES-17, ES-18, and ES-19) One (1) Lamination Line (ID No. ES-31)

The following table provides a summary of limits and standards for the emission source(s) describe above:

Pollutant	Limits/Standards	Applicable Regulation
Hazardous air	National Emission Standards for Hazardous Air Pollutants:	15A NCAC 02D .1111
pollutants	Paper and Other Web Coatings	40 CFR 63, Subpart JJJJ

#### 1. 15A NCAC 2D .1111: MAXIMUM ACHIEVABLE CONTROL TECHNOLOGY

#### Applicability [40 CFR 63.3290 and .3300]

a. For the affected source, defined as the collection of all web coating lines at the facility (ID Nos. ES-1, ES-17, ES-18, ES-19 and ES-31) the Permittee shall comply with all requirements of 15A NCAC 2D .1111 "Maximum Achievable Control Technology" and 40 CFR 63, including Subpart JJJJ "National Emission Standards for Hazardous Air Pollutants: Paper and Other Web Coating," and Subpart A "General Provisions."

#### **Definitions and Nomenclature**

b. For the purpose of this permit condition, the definitions and nomenclature contained in 40 CFR 63.3310 shall apply. [40 CFR 63.3310]

#### 40 CFR Part 63 Subpart A General Provisions

c. The Permittee shall comply with the requirements of 40 CFR 63 Subpart A General Provisions according to Table 2 to 40 CFR Part 63 Subpart JJJJ. [40 CFR 63.3340(d)]

#### <u>Testing</u> [15A NCAC 02Q .0508(b)]

d. If emissions testing is required, the testing shall be performed in accordance General Condition JJ. If the results of this test are above the limit given in Section 2.2 A.1.f below, the Permittee shall be deemed in noncompliance with 15A NCAC 02D .1111.

#### **General Compliance Requirements**

- e. The following general compliance requirements apply:
  - i. Each source shall be in compliance with the emission limits specified in Section 2.2 A.1.f below at all times, including periods of startup, shutdown, and malfunction. [40 CFR 63.3340(a)]
  - ii. The Permittee shall operate and maintain the affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require the Permittee to make any further efforts to reduce emissions if levels required by the applicable standard have been achieved. Determination of whether a source is operating in compliance with operation and maintenance requirements will be based on information available to the DAQ which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source. [40 CFR 63.3340(b)]

#### Emission Standards [15A NCAC 02Q .0508(b)]

- f. The Permittee shall limit organic Hazardous Air Pollutant (HAP) emissions from the web coating lines to the levels specified below for all periods of operation, including startup shutdown and malfunction (SSM):
  - i. No more than 1.6 percent of the mass of coating materials applied for each month [40CFR 63.3320(b)(2)]; or
  - ii. No more than 8 percent of the mass of coating solids applied for each month. [40CFR 63.3320(b)(3)]

#### Compliance Demonstration Requirements [15A NCAC 02Q .0508(b)]

g. The Permittee shall demonstrate compliance each month with the emission limitations in Section 2.2 A.1.f above. For each monthly demonstration, the Permittee may apply any combination of the emission limitations to each of the web coating lines individually, to each of one or more groupings of the lines (including a single grouping encompassing all lines), or to any combination of individual and grouped lines, so long as each web coating line is included in the compliance demonstration for the month (i.e., the Permittee is not required to apply the same emission limitation to each of the individual lines or groups of lines). The Permittee may change the emission limitation that apply each month to the individual or grouped lines and may change line groupings for the monthly compliance demonstration. [40 CFR 63.3370(a)]

- h. The Permittee shall use one of the following compliance demonstration methods: [40 CFR 63.3370(a)]
  - i. As-purchased "compliant" coating materials
    - (A) If the Permittee chooses to comply by using coating materials that individually meet the emission standards in Section 2.2 A.1.f above, the Permitee shall demonstrate that each coating material applied during the month contains no more than 0.016 mass fraction organic HAP or 0.08 kg organic HAP per kg coating solids on an as-purchased basis as determined in accordance with 40 CFR 63.3360(c).
    - (B) The Permittee shall be deemed in compliance with the emission standards in Section 2.2 A.1.f above if each coating material applied is applied as-purchased and contains no more than 0.016 kg organic HAP per kg coating material or 0.08 kg organic HAP per kg coating solids.
    - [40 CFR 63.3370(b)]
  - ii. As-applied "compliant" coating materials
    - (A) If the Permittee chooses to comply by using coating materials that meet the emission standards in Section 2.2 A.1.f above as-applied, the Permittee shall demonstrate compliance by following one of the procedures in 40 CFR 63.3370(c)(1) through (4). Compliance is determined in accordance with (B) below.
    - (B) The Permittee shall be deemed in compliance with the emission standards in Section 2.2 A.1.f if:
      (1) the organic HAP content of each coating material as-applied is no more than 0.016 kg organic HAP per kg coating material or 0.08 kg organic HAP per kg coating solids; or
      - (2) the monthly average organic HAP content of all as-applied coating materials are no more than 0.016 kg organic HAP per kg coating material or 0.08 kg organic HAP per kg coating solids.
    - [40 CFR 63.3370(c)]
  - iii. Monthly allowable organic HAP applied The Permittee may demonstrate that the total monthly organic HAP applied as determined by Equation 10 at 40 CFR 63.3370(d) is less than the calculated equivalent allowable organic HAP as determined by Equation 17 or 18 at 40 CFR 63.3370(m). [40 CFR 63.3370(d)]
  - iv. Volatile organic and coating solids content

If the Permittee chooses to use the volatile organic content as a surrogate for the organic HAP content of coatings, the Permittee shall determine the as-purchased volatile organic content and coating solids content of each coating material applied by following the procedures in 40 CFR 63.3360 (d)(1) or (2), and the as-applied volatile organic content and coating solids content of each coating material by following the procedures in 40 CFR 63.3360(d)(3). [40 CFR 63.3360(d)]

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if one of these compliance requirements are not met or if a compliance demonstration indicates an exceedance of the relevant standard in Section 2.2 A.1.f above.

#### Recordkeeping [15A NCAC 02Q .0508(f)]

- i. The Permittee shall maintain the following records on a monthly basis [40 CFR 63.3410(a)]:
  - i. organic HAP content data for the purpose of demonstrating compliance in accordance with the requirements of 40 CFR 63.3360(c). [40 CFR 63.3410(a)(1)(iii)]
  - ii. volatile matter and coating solids content data for the purpose of demonstrating compliance in accordance with the requirements of 40 CFR 63.3360(d). [40 CFR 63.3410(a)(1)(iv)]
  - iii. material usage, organic HAP usage, volatile matter usage, and coating solids usage and compliance demonstrations using these data in accordance with the requirements of Section 2.2 A.1.h. [40 CFR 63.3410(a)(1)(vi)]

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if these recordkeeping requirements are not met.

j. The Permittee shall maintain files of all information (including all reports and notifications) required in Section 2.2. A.1.i above recorded in a form suitable and readily available for expeditious inspection and review. The files shall be retained for at least 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record. At a minimum, the most recent 2 years of data shall be retained on site. The remaining 3 years of data may be retained off site. Such files may be maintained on microfilm, on a computer, on computer floppy disks, on magnetic tape disks, or on microfiche. [40 CFR 63.3410(a), 63.10(b)(1)] The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if this recordkeeping requirement is not met.

#### Reporting [15A NCAC 02Q .0508(f)]

- k. The following reporting requirements apply:
  - i. The Permittee shall submit a semi-annual compliance report, of the monitoring and recordkeeping activities postmarked on or before January 30 of each calendar year for the preceding six-month period between July and December, and July 30 of each calendar year for the preceding six-month period between January and June. [40 CFR 63.3400(c)(1)]
  - ii. The report shall contain the following:
    - (A) Company name and address.
    - (B) Statement by a responsible official with that official's name, title, and signature certifying the accuracy of the content of the report.
    - (C) Date of report and beginning and ending dates of the reporting period.
    - (D) If there are no deviations from any emission limitations that apply, a statement that there were no deviations from the emission limitations during the reporting period.
    - (E) For each deviation from an emission limitation that applies, the compliance report must also contain the following information:
      - (1) the total operating time of the web coating line(s) during the reporting period.
      - (2) information on the number, duration, and cause of deviations (including unknown cause), if applicable, and the corrective action taken.
      - (3) an estimate of the quantity of each regulated pollutant emitted over the emission limits in Section 2.2 A.1.f for each monthly period covered in the report if the source failed to an applicable emission limit in Section 2.2 A.1.f.
    - [40 CFR 63.3400(c)(2)]
  - iii. The reports shall also be submitted to the EPA as follows: Prior to the electronic template being available in CEDRI for one year, the report must be postmarked or delivered by the dates in paragraph (k)(i) above. After the electronic template has been available in CEDRI for 1 year, the next full report shall be submitted electronically as described in 40 CFR 63.3400(h). [40 CFR 63.3400(c)(1)(ii)]

The Permittee shall be deemed in noncompliance with 15A NCAC 2D .1111 if these reporting requirements are not met.

## B. Saturator process operation (ID Nos. ES-1, ES-17, ES-18, and ES-19) Pre-press operation (ID Nos. ES-3505, ES-3503, ES-3516, and ES-3502) Heavy Duty Graphics Arts Foam Board Process consisting of glue mixing, lift tables, roll coater, conveying, and cold press pods (ID No. ES-29)

The following table provides a summary of limits and standards for the emission source(s) described above:

Pollutant	Limits/Standards	Applicable Regulation
Toxic air	State-enforceable only	15A NCAC 02D .1100
pollutants	Modeled emission limits	

#### State-enforceable only

#### 1. 15A NCAC 02D .1100: CONTROL OF TOXIC AIR POLLUTANTS

a. The Permittee has submitted a toxic air pollutant dispersion modeling analysis dated April 19, 2005 or the facility's toxic air pollutant emissions as listed in the table below. The modeling analysis was reviewed and approved by the AQAB on June 07, 2005. Placement of the emission sources, configuration of the emission points, and operation of the sources shall be in accordance with the submitted dispersion modeling analysis and should reflect any changes from the original analysis submittal as outlined in the AQAB review memo.

Emission Source ID No. or Group	Ammonia (lb/hr)	Formaldehyde (lb/hr)	1,3 Butadiene (lb/yr)	Phenol* (lb/hr)
Saturator process operation Saturator Dryer (ID No. ES-1) mixing tank 1 (ID No. ES-17) mixing tank 2 (ID No. ES-18, and mixing tank 3 (ID No. ES-19)	3.23	12.83	71.2	
Pre-press operations (ID Nos. ES-3505, ES- 3503, ES-3516, and ES-3502) including: No. 2 15 open pre-press (ID No. ES-5), 10 open pre-press (ID No. ES-9), No. 1 15 open pre-press (ID No. ES-10), and 9 open pre- press (ID No. ES-23)	0.19	6.38		
Heavy Duty Graphics Arts Foam Board Process (ID No. ES-29)				5.25

\* Phenol was added to table as a result of permit modification 03700T18

- a. Compliance with the above limits shall be based on:
  - i. for the saturator process operations (**ID Nos. ES-1, ES-17, ES-18, and ES-19**), monthly production and material usage data with toxic air pollutant emissions calculated using standard engineering methodology (e.g., material balance, stack test data).
  - ii. for the pre-press operations (**ID Nos. ES-3505, ES-3503, ES-3516, and ES-3502**), the treated paper from the saturator operations processed shall not exceed 45,892 square feet per hour.
  - iii. for the Heavy Duty Graphics Arts Foam Board Process (**ID No. ES-29**), if the Phenol content used in the adhesive for the coating exceed 3% by weight, the facility shall monitor and record the emissions of Phenol from this source on a daily basis as per 2.2 B.1.c, below.
- b. The Permittee shall maintain the following records on a monthly basis to determine compliance with the above limits.
  - i. for the saturator process operations (**ID Nos. ES-1, ES-17, ES-18, and ES-19**), records of operating data, material usage data, and other information as appropriate for each month,
  - ii. for the saturator process operations (**ID Nos. ES-17, ES-18, and ES-19**), records of formaldehyde and ammonia emissions, with supporting calculations, calculated as monthly emissions divided by saturator process operation monthly hours of operation,
  - iii. for the saturator process operations (**ID Nos. ES-17, ES-18, and ES-19**), records of 1,3 butadiene emissions, with supporting calculations, calculated as a 12-month rolling total of monthly emissions,
  - iv. for the pre-press operations (**ID** Nos. 3502, 3503, 3516, and 3505), records of operating data and the amount of treated paper processed.
- c. If required to monitor and record the emissions of Phenol from the Heavy Duty Graphics Arts Foam Board Process (ID

**No. ES-29**), the Permittee shall maintain records of the amount of heavy duty graphics arts foam board processed per day, the daily emissions of Phenol from this source, and also the maximum hourly emissions of Phenol for that day. The Permittee shall be in violation of 15A NCAC 02D .1100 if the ever the maximum hourly emissions of Phenol exceed 5.25 pounds per hour.

d. For compliance purposes, within 30 days after each calendar year quarter the Permittee shall report the monthly records of toxic air pollutant emissions from the saturator process operations (**ID Nos. ES-17, ES-18, and ES-19**) and the amount of treated paper processed in the pre-press operations (**ID Nos. 3502, 3503, 3516, and 3505**).

#### C. Facility-Wide sources

The following table provides a summary of limits and standards for the emission source(s) described above:

Pollutant	Limits/Standards	Applicable Regulation
Toxic air	State-enforceable only	15A NCAC 02D .1100
pollutants	Toxic Permit Emission Rates	
Odors	State-enforceable only	15A NCAC 02D .1806
	Odorous emissions must be controlled.	

#### State-enforceable only

#### 1. 15A NCAC 02Q .0711: EMISSION RATES REQUIRING A PERMIT

- a. The facility shall be operated and maintained in such a manner that any new, existing or increased actual emissions of any Toxic Air Pollutant (TAP) listed in 15A NCAC 02Q .0711 or in this permit from all sources at the facility (excluding those sources exempt under 15A NCAC 02Q .0702 "Exemptions"), including fugitive emissions and emission sources not otherwise required to have a permit, will not exceed its respective TAP permitting emission rates (TPER) listed in 15A NCAC 02Q .0711 without first obtaining an air permit to construct or operate.
- b. PRIOR to exceeding any of the TPERs listed in 15A NCAC 02Q .0711, the Permittee shall be responsible for obtaining an air permit to emit TAPs and for demonstrating compliance with the requirements found in 15A NCAC 02D .1100 "Control of Toxic Air Pollutants."
- c. The Permittee shall maintain at the facility records of operational information sufficient for demonstrating to the Division of Air Quality staff that actual TAPs are less than the rate listed in 15A NCAC 02Q .0711.
- d. The TPER table listed below is provided to assist the Permittee in determining when an air permit is required pursuant to 15A NCAC 02Q .0711 and may not represent all TAPs being emitted from the facility. This table will be updated at such time as the permit is either modified or renewed.

Pollutant	CAS No.	Carcinogens (lb/yr)	Chronic Toxicant (lb/day)	Acute Systemic Toxicants (lb/hr)	Acute Irritants (lb/hr)
Acetaldehyde	75-07-0				6.8
1,4 Dioxane	123-91-1		12		
Ethylene oxide	75-21-8	1.8			
n-hexane	110-54-3		23		
Styrene	100-42-5			2.7	
Toluene	108-88-3		98		

#### 2. State-enforceable only

#### 15A NCAC 02D .1806: CONTROL AND PROHIBITION OF ODOROUS EMISSIONS

The Permittee shall not operate the facility without implementing management practices or installing and operating odor control equipment sufficient to prevent odorous emissions from the facility from causing or contributing to objectionable odors beyond the facility's boundary.

## SECTION 3 - INSIGNIFICANT ACTIVITIES PER 15A NCAC 02Q .0503(8)

Emission Source ID No.	Emission Source Description <sup>1,2</sup>
IES-PAT	Two (2) polyvinyl acetate tanks (6,000 gallons, each)
IES-MST	One material storage tank (6,000 gallons)
IES-11	Two vacuum units each unit venting to a cyclone (ID Nos. ICD-10 and ICD-32)
I6	One 7,000 gallon glue tank
I7	12 natural gas-fired heaters used for comfort heat
18	One (1,000 gallon) propane storage tank
19	Small press (18 inches by 24 inches) for research sample
I10	Parts Washer (15 gallon parts washer using a low VOC cleaning agent)
IES-14	One bulk resin tank (15,192 gallons capacity)
IES-15	One bulk resin tank (15,000 gallons capacity)
IES-16	One bulk resin tank (7,527 gallons capacity)
IES-2	Gatorfoam production operation – One (1) Gatorfoam saw controlled by one fabric filter (800 square feet of filter area, ID No. CD-106)
IES-4 NSPS IIII MACT ZZZZ	Diesel-fired emergency fire pump (175-hp)
IES-8 NSPS JJJJ MACT ZZZZ	Natural gas fired emergency generator (80kw)

<sup>1</sup>Because an activity is insignificant does not mean that the activity is exempted from an applicable requirement (Federal or State) or that the Permittee is exempted from demonstrating compliance with any applicable requirement.

<sup>2</sup> When applicable, emissions from stationary source activities identified above shall be included in determining compliance with the permit requirements for toxic air pollutants under 15A NCAC 02D .1100 "Control of Toxic Air Pollutants" or 02Q .0711 "Emission Rates Requiring a Permit."

## SECTION 4 - GENERAL CONDITIONS (version 7.0, 08/21/2023)

This section describes terms and conditions applicable to this Title V facility.

#### A. General Provisions [NCGS 143-215 and 15A NCAC 02Q .0508(i)(16)]

- 1. Terms not otherwise defined in this permit shall have the meaning assigned to such terms as defined in 15A NCAC 02D and 02Q.
- 2. The terms, conditions, requirements, limitations, and restrictions set forth in this permit are binding and enforceable pursuant to NCGS 143-215.114A and 143-215.114B, including assessment of civil and/or criminal penalties. Any unauthorized deviation from the conditions of this permit may constitute grounds for revocation and/or enforcement action by the DAQ.
- 3. This permit is not a waiver of or approval of any other Department permits that may be required for other aspects of the facility which are not addressed in this permit.
- 4. This permit does not relieve the Permittee from liability for harm or injury to human health or welfare, animal or plant life, or property caused by the construction or operation of this permitted facility, or from penalties therefore, nor does it allow the Permittee to cause pollution in contravention of state laws or rules, unless specifically authorized by an order from the North Carolina Environmental Management Commission.
- 5. Except as identified as state-only requirements in this permit, all terms and conditions contained herein shall be enforceable by the DAQ, the EPA, and citizens of the United States as defined in the Federal Clean Air Act.
- 6. Any stationary source of air pollution shall not be operated, maintained, or modified without the appropriate and valid permits issued by the DAQ, unless the source is exempted by rule. The DAQ may issue a permit only after it receives reasonable assurance that the installation will not cause air pollution in violation of any of the applicable requirements. A permitted installation may only be operated, maintained, constructed, expanded, or modified in a manner that is consistent with the terms of this permit.

#### B. Permit Availability [15A NCAC 02Q .0507(k) and .0508(i)(9)(B)]

The Permittee shall have available at the facility a copy of this permit and shall retain for the duration of the permit term one complete copy of the application(s) and any information submitted in support of the application package. The permit and application shall be made available to an authorized representative of the Department of Environmental Quality upon request.

#### C. Severability Clause [15A NCAC 02Q .0508(i)(2)]

In the event of an administrative challenge to a final and binding permit in which a condition is held to be invalid, the provisions in this permit are severable so that all requirements contained in the permit, except those held to be invalid, shall remain valid and must be complied with.

#### D. Submissions [15A NCAC 02Q .0507(e) and 02Q .0508(i)(16)]

Except as otherwise specified herein, two copies of all documents, reports, test data, monitoring data, notifications, request for renewal, and any other information required by this permit shall be submitted to the appropriate Regional Office. Refer to the Regional Office address on the cover page of this permit. For continuous emissions monitoring systems (CEMS) reports, continuous opacity monitoring systems (COMS) reports, quality assurance (QA)/quality control (QC) reports, acid rain CEM certification reports, and NOx budget CEM certification reports, one copy shall be sent to the appropriate Regional Office and one copy shall be sent to:

Supervisor, Stationary Source Compliance North Carolina Division of Air Quality 1641 Mail Service Center Raleigh, NC 27699-1641

All submittals shall include the facility name and Facility ID number (refer to the cover page of this permit).

#### E. Duty to Comply [15A NCAC 02Q .0508(i)(3)]

The Permittee shall comply with all terms, conditions, requirements, limitations and restrictions set forth in this permit. Noncompliance with any permit condition except conditions identified as state-only requirements constitutes a violation of the Federal Clean Air Act. Noncompliance with any permit condition is grounds for enforcement action, for permit termination, revocation and reissuance, or modification, or for denial of a permit renewal application.

#### F. <u>Circumvention</u> - STATE ENFORCEABLE ONLY

The facility shall be properly operated and maintained at all times in a manner that will effect an overall reduction in air pollution. Unless otherwise specified by this permit, no emission source may be operated without the concurrent operation of its associated air pollution control device(s) and appurtenances.

#### G. Title V Permit Modifications

- Administrative Permit Amendments [15A NCAC 02Q .0514] The Permittee shall submit an application for an administrative permit amendment in accordance with 15A NCAC 02Q .0514.
- Transfer in Ownership or Operation and Application Submittal Content [15A NCAC 02Q .0524 and 02Q .0505] The Permittee shall submit an application for an ownership change in accordance with 15A NCAC 02Q.0524 and 02Q .0505.
- 3. Minor Permit Modifications [15A NCAC 02Q .0515]
- The Permittee shall submit an application for a minor permit modification in accordance with 15A NCAC 02Q .0515. 4. Significant Permit Modifications [15A NCAC 02Q .0516]
- The Permittee shall submit an application for a significant permit modification in accordance with 15A NCAC 02Q .0516.
- Reopening for Cause [15A NCAC 02Q .0517] The Permittee shall submit an application for reopening for cause in accordance with 15A NCAC 02Q .0517.

#### H. Changes Not Requiring Permit Modifications

- 1. Reporting Requirements [15A NCAC 02Q .0508(f)]
  - Any of the following that would result in new or increased emissions from the emission source(s) listed in Section 1 must be reported to the Regional Supervisor, DAQ:
  - a. changes in the information submitted in the application;
  - b. changes that modify equipment or processes; or
  - c. changes in the quantity or quality of materials processed.

If appropriate, modifications to the permit may then be made by the DAQ to reflect any necessary changes in the permit conditions. In no case are any new or increased emissions allowed that will cause a violation of the emission limitations specified herein.

- 2. Section 502(b)(10) Changes [15A NCAC 02Q .0523(a)]
  - a. "Section 502(b)(10) changes" means changes that contravene an express permit term or condition. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), recordkeeping, reporting, or compliance certification requirements.
  - b. The Permittee may make Section 502(b)(10) changes without having the permit revised if:
    - i. the changes are not a modification under Title I of the Federal Clean Air Act;
    - ii. the changes do not cause the allowable emissions under the permit to be exceeded;
    - iii. the Permittee notifies the Director and EPA with written notification at least seven days before the change is made; and
    - iv. the Permittee shall attach the notice to the relevant permit.
  - c. The written notification shall include:
    - i. a description of the change;
    - ii. the date on which the change will occur;
    - iii. any change in emissions; and
    - iv. any permit term or condition that is no longer applicable as a result of the change.
  - d. Section 502(b)(10) changes shall be made in the permit the next time that the permit is revised or renewed, whichever comes first.
- 3. Off Permit Changes [15A NCAC 02Q .0523(b)]
  - The Permittee may make changes in the operation or emissions without revising the permit if:
  - a. the change affects only insignificant activities and the activities remain insignificant after the change; or
  - b. the change is not covered under any applicable requirement.
- 4. Emissions Trading [15A NCAC 02Q .0523(c)]

To the extent that emissions trading is allowed under 15A NCAC 02D, including subsequently adopted maximum achievable control technology standards, emissions trading shall be allowed without permit revision pursuant to 15A NCAC 02Q .0523(c).

#### I.A <u>Reporting Requirements for Excess Emissions [15A NCAC 02D .0535(f) and 02Q .0508(f)(2)]</u>

- 1. <u>"Excess Emissions"</u> means an emission rate that exceeds any applicable emission limitation or standard allowed by any rule in Sections .0500, .0900, .1200, or .1400 of Subchapter 02D; or by a permit condition; or that exceeds an emission limit established in a permit issued under 15A NCAC 02Q .0700. (*Note: Definitions of excess emissions under 02D .1110 and 02D .1111 shall apply where defined by rule.*)
- 2. If a source is required to report excess emissions under NSPS (15A NCAC 02D .0524), NESHAPS (15A NCAC 02D .1110 or .1111), or the operating permit provides for periodic (e.g., quarterly) reporting of excess emissions, reporting shall be performed as prescribed therein.
- 3. If the source is not subject to NSPS (15A NCAC 02D .0524), NESHAPS (15A NCAC 02D .1110 or .1111), or these rules do NOT define "excess emissions," the Permittee shall report excess emissions in accordance with 15A NCAC 02D .0535 as follows:
  - a. Pursuant to 15A NCAC 02D .0535, if excess emissions last for more than four hours resulting from a malfunction, a breakdown of process or control equipment, or any other abnormal condition, the owner or operator shall:
    - notify the Regional Supervisor or Director of any such occurrence by 9:00 a.m. Eastern Time of the Division's next business day of becoming aware of the occurrence and provide:
      - name and location of the facility;
      - nature and cause of the malfunction or breakdown;
      - time when the malfunction or breakdown is first observed;
      - expected duration; and
      - estimated rate of emissions;
    - ii. notify the Regional Supervisor or Director immediately when corrective measures have been accomplished; and
    - iii. submit to the Regional Supervisor or Director within 15 days a written report as described in 15A NCAC 02D .0535(f)(3).

#### I.B Reporting Requirements for Permit Deviations [15A NCAC 02D .0535(f) and 02Q .0508(f)(2)]

- 1. "<u>Permit Deviations</u>" for the purposes of this condition, any action or condition not in accordance with the terms and conditions of this permit including those attributable to upset conditions as well as excess emissions as defined above lasting less than four hours.
- 2. Pursuant to 15A NCAC 02Q .0508(f)(2), the Permittee shall report deviations from permit requirements (terms and conditions) quarterly by notifying the Regional Supervisor or Director of all other deviations from permit requirements not covered under 15A NCAC 02D .0535. A written report to the Regional Supervisor shall include the probable cause of such deviation and any corrective actions or preventative actions taken. The responsible official shall certify all deviations from permit requirements.

#### I.C Other Requirements under 15A NCAC 02D .0535

The Permittee shall comply with all other applicable requirements contained in 15A NCAC 02D .0535, including 15A NCAC 02D .0535(c) as follows:

- 1. Any excess emissions that do not occur during start-up and shut-down shall be considered a violation of the appropriate rule unless the owner or operator of the sources demonstrates to the Director that the excess emissions are a result of a malfunction. The Director shall consider, along with any other pertinent information, the criteria contained in 15A NCAC 02D .0535(c)(1) through (7).
- 2. 15A NCAC 02D .0535(g). Excess emissions during start-up and shut-down shall be considered a violation of the appropriate rule if the owner or operator cannot demonstrate that excess emissions are unavoidable.

#### J. RESERVED

#### K. Permit Renewal [15A NCAC 02Q .0508(e) and 02Q .0513(b)]

This 15A NCAC 02Q .0500 permit is issued for a fixed term not to exceed five years and shall expire at the end of its term. Permit expiration terminates the facility's right to operate unless a complete 15A NCAC 02Q .0500 renewal application is submitted at least six months before the date of permit expiration. If the Permittee or applicant has complied with 15A NCAC 02Q .0512(b)(1), this 15A NCAC 02Q .0500 permit shall not expire until the renewal permit has been issued or denied. Permit expiration under 15A NCAC 02Q .0400 terminates the facility's right to operate unless a complete

15A NCAC 02Q .0400 renewal application is submitted at least six months before the date of permit expiration for facilities subject to 15A NCAC 02Q .0400 requirements. In either of these events, all terms and conditions of these permits shall remain in effect until the renewal permits have been issued or denied.

#### L. Need to Halt or Reduce Activity Not a Defense [15A NCAC 02Q .0508(i)(4)]

It shall not be a defense for a Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

#### M. Duty to Provide Information (submittal of information) [15A NCAC 02Q .0508(i)(9)]

- 1. The Permittee shall furnish to the DAQ, in a timely manner, any reasonable information that the Director may request in **writing** to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit.
- 2. The Permittee shall furnish the DAQ copies of records required to be kept by the permit when such copies are requested by the Director. For information claimed to be confidential, the Permittee may furnish such records directly to the EPA upon request along with a claim of confidentiality.

#### N. Duty to Supplement [15A NCAC 02Q .0507(f)]

The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to the DAQ. The Permittee shall also provide additional information as necessary to address any requirement that becomes applicable to the facility after the date a complete permit application was submitted but prior to the release of the draft permit.

#### O. <u>Retention of Records</u> [15A NCAC 02Q .0508(f) and 02Q .0508(l)]

The Permittee shall retain records of all required monitoring data and supporting information for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring information, and copies of all reports required by the permit. These records shall be maintained in a form suitable and readily available for expeditious inspection and review. Any records required by the conditions of this permit shall be kept on site and made available to DAQ personnel for inspection upon request.

#### P. Compliance Certification [15A NCAC 02Q .0508(n)]

The Permittee shall submit to the DAQ and the EPA (Air Enforcement Branch, EPA, Region 4, 61 Forsyth Street SW, Atlanta, GA 30303 or through the EPA CEDRI) postmarked on or before March 1 a compliance certification (for the preceding calendar year) by a responsible official with all terms and conditions in the permit (including emissions limitations, standards, or work practices), except for conditions identified as being State-enforceable Only. It shall be the responsibility of the current owner to submit a compliance certification for the entire year regardless of who owned the facility during the year. The compliance certification shall comply with additional requirements as may be specified under Sections 114(a)(3) or 504(b) of the Federal Clean Air Act. The compliance certification shall specify:

- 1. the identification of each term or condition of the permit that is the basis of the certification;
- 2. the compliance status (with the terms and conditions of the permit for the period covered by the certification);
- 3. whether compliance was continuous or intermittent;
- 4. the method(s) used for determining the compliance status of the source during the certification period;
- 5. each deviation and take it into account in the compliance certification; and
- 6. as possible exceptions to compliance, any periods during which compliance is required and in which an excursion or exceedance as defined under 40 CFR Part 64 (CAM) occurred.

#### Q. Certification by Responsible Official [15A NCAC 02Q .0520]

A responsible official shall certify the truth, accuracy, and completeness of any application form, report, or compliance certification required by this permit. All certifications shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

#### R. Permit Shield for Applicable Requirements [15A NCAC 02Q .0512]

- 1. Compliance with the terms and conditions of this permit shall be deemed compliance with applicable requirements, where such applicable requirements are included and specifically identified in the permit as of the date of permit issuance.
- 2. A permit shield shall not alter or affect:

- a. the power of the Commission, Secretary of the Department, or Governor under NCGS 143-215.3(a)(12), or EPA under Section 303 of the Federal Clean Air Act;
- b. the liability of an owner or operator of a facility for any violation of applicable requirements prior to the effective date of the permit or at the time of permit issuance;
- c. the applicable requirements under Title IV; or
- d. the ability of the Director or the EPA under Section 114 of the Federal Clean Air Act to obtain information to determine compliance of the facility with its permit.
- 3. A permit shield does not apply to any change made at a facility that does not require a permit or permit revision made under 15A NCAC 02Q .0523.
- 4. A permit shield does not extend to minor permit modifications made under 15A NCAC 02Q .0515.

#### S. Termination, Modification, and Revocation of the Permit [15A NCAC 02Q .0519]

The Director may terminate, modify, or revoke and reissue this permit if:

- 1. the information contained in the application or presented in support thereof is determined to be incorrect;
- 2. the conditions under which the permit or permit renewal was granted have changed;
- 3. violations of conditions contained in the permit have occurred;
- 4. the EPA requests that the permit be revoked under 40 CFR 70.7(g) or 70.8(d); or
- 5. the Director finds that termination, modification, or revocation and reissuance of the permit is necessary to carry out the purpose of NCGS Chapter 143, Article 21B.

#### T. Insignificant Activities [15A NCAC 02Q .0503]

Because an emission source or activity is insignificant does not mean that the emission source or activity is exempted from any applicable requirement or that the owner or operator of the source is exempted from demonstrating compliance with any applicable requirement. The Permittee shall have available at the facility at all times and made available to an authorized representative upon request, documentation, including calculations, if necessary, to demonstrate that an emission source or activity is insignificant.

#### U. Property Rights [15A NCAC 02Q .0508(i)(8)]

This permit does not convey any property rights in either real or personal property or any exclusive privileges.

#### V. Inspection and Entry [15A NCAC 02Q .0508(l) and NCGS 143-215.3(a)(2)]

- 1. Upon presentation of credentials and other documents as may be required by law, the Permittee shall allow the DAQ, or an authorized representative, to perform the following:
  - a. enter the Permittee's premises where the permitted facility is located or emissions-related activity is conducted, or where records are kept under the conditions of the permit;
  - b. have access to and copy, at reasonable times, any records that are required to be kept under the conditions of the permit;
  - c. inspect at reasonable times and using reasonable safety practices any source, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
  - d. sample or monitor substances or parameters, using reasonable safety practices, for the purpose of assuring compliance with the permit or applicable requirements at reasonable times.

Nothing in this condition shall limit the ability of the EPA to inspect or enter the premises of the Permittee under Section 114 or other provisions of the Federal Clean Air Act.

2. No person shall refuse entry or access to any authorized representative of the DAQ who requests entry for purposes of inspection, and who presents appropriate credentials, nor shall any person obstruct, hamper, or interfere with any such authorized representative while in the process of carrying out his official duties. Refusal of entry or access may constitute grounds for permit revocation and assessment of civil penalties.

#### W. Annual Fee Payment [15A NCAC 02Q .0508(i)(10)]

- 1. The Permittee shall pay all fees in accordance with 15A NCAC 02Q .0200.
- 2. Payment of fees may be by check or money order made payable to the N.C. Department of Environmental Quality. Annual permit fee payments shall refer to the permit number.
- 3. If, within 30 days after being billed, the Permittee fails to pay an annual fee, the Director may initiate action to terminate the permit under 15A NCAC 02Q .0519.

Permit 03700T24 Page 29

#### X. Annual Emission Inventory Requirements [15A NCAC 02Q .0207]

The Permittee shall report by **June 30 of each year** the actual emissions of each air pollutant listed in 15A NCAC 02Q .0207(a) from each emission source within the facility during the previous calendar year. The report shall be in or on such form as may be established by the Director. The accuracy of the report shall be certified by a responsible official of the facility.

#### Y. Confidential Information [15A NCAC 02Q .0107 and 02Q .0508(i)(9)]

Whenever the Permittee submits information under a claim of confidentiality pursuant to 15A NCAC 02Q .0107, the Permittee may also submit a copy of all such information and claim directly to the EPA upon request. All requests for confidentiality must be in accordance with 15A NCAC 02Q .0107.

#### Z. Construction and Operation Permits [15A NCAC 02Q .0100 and .0300]

A construction and operating permit shall be obtained by the Permittee for any proposed new or modified facility or emission source which is not exempted from having a permit prior to the beginning of construction or modification, in accordance with all applicable provisions of 15A NCAC 02Q .0100 and .0300.

#### AA. Standard Application Form and Required Information [15A NCAC 02Q .0505 and .0507]

The Permittee shall submit applications and required information in accordance with the provisions of 15A NCAC 02Q .0505 and .0507.

#### BB. Financial Responsibility and Compliance History [15A NCAC 02Q .0507(d)(3)]

The DAQ may require an applicant to submit a statement of financial qualifications and/or a statement of substantial compliance history.

#### CC. Refrigerant Requirements (Stratospheric Ozone and Climate Protection) [15A NCAC 02Q .0501(d)]

- I. If the Permittee has appliances or refrigeration equipment, including air conditioning equipment, which use Class I or II ozone-depleting substances such as chlorofluorocarbons and hydrochlorofluorocarbons listed as refrigerants in 40 CFR Part 82 Subpart A Appendices A and B, the Permittee shall service, repair, and maintain such equipment according to the work practices, personnel certification requirements, and certified recycling and recovery equipment specified in 40 CFR Part 82 Subpart F.
- 2. The Permittee shall not knowingly vent or otherwise release any Class I or II substance into the environment during the repair, servicing, maintenance, or disposal of any such device except as provided in 40 CFR Part 82 Subpart F.
- 3. The Permittee shall comply with all reporting and recordkeeping requirements of 40 CFR 82.166. Reports shall be submitted to the EPA or its designee as required.

#### DD. Prevention of Accidental Releases - Section 112(r) [15A NCAC 02Q .0508(h)]

If the Permittee is required to develop and register a Risk Management Plan with EPA pursuant to Section 112(r) of the Clean Air Act, then the Permittee is required to register this plan in accordance with 40 CFR Part 68.

#### EE. National Emission Standards Asbestos – 40 CFR Part 61, Subpart M [15A NCAC 02D .1110]

The Permittee shall comply with all applicable standards for demolition and renovation activities pursuant to the requirements of 40 CFR Part 61, Subpart M. The permittee shall not be required to obtain a modification of this permit in order to perform the referenced activities.

#### FF. Title IV Allowances [15A NCAC 02Q .0508(i)(1)]

This permit does not limit the number of Title IV allowances held by the Permittee, but the Permittee may not use allowances as a defense to noncompliance with any other applicable requirement. The Permittee's emissions may not exceed any allowances that the facility lawfully holds under Title IV of the Federal Clean Air Act.

#### GG. Air Pollution Emergency Episode [15A NCAC 02D .0300]

Should the Director of the DAQ declare an Air Pollution Emergency Episode, the Permittee will be required to operate in accordance with the Permittee's previously approved Emission Reduction Plan or, in the absence of an approved plan, with the appropriate requirements specified in 15A NCAC 02D .0300.

Permit 03700T24 Page 30

#### HH. Registration of Air Pollution Sources [15A NCAC 02D .0202]

The Director of the DAQ may require the Permittee to register a source of air pollution. If the Permittee is required to register a source of air pollution, this registration and required information will be in accordance with 15A NCAC 02D .0202(b).

#### II. Ambient Air Quality Standards [15A NCAC 02D .0501(c)]

In addition to any control or manner of operation necessary to meet emission standards specified in this permit, any source of air pollution shall be operated with such control or in such manner that the source shall not cause the ambient air quality standards in 15A NCAC 02D .0400 to be exceeded at any point beyond the premises on which the source is located. When controls more stringent than named in the applicable emission standards in this permit are required to prevent violation of the ambient air quality standards or are required to create an offset, the permit shall contain a condition requiring these controls.

#### JJ. General Emissions Testing and Reporting Requirements [15A NCAC 02Q .0508(i)(16)]

Emission compliance testing shall be by the procedures of Section .2600, except as may be otherwise required in Rules .0524, .1110, or .1111 of Subchapter 02D. If emissions testing is required by this permit or the DAQ or if the Permittee submits emissions testing to the DAQ to demonstrate compliance for emission sources subject to Rules .0524, .1110, or .1111, the Permittee shall provide and submit all notifications, conduct all testing, and submit all test reports in accordance with the requirements of 15A NCAC 02D .0524, .1110, or .1111, as applicable. Otherwise, if emissions testing is required by this permit or the DAQ or if the Permittee submits emissions testing to the DAQ to demonstrate compliance, the Permittee shall perform such testing in accordance with 15A NCAC 02D .2600 and follow the procedures outlined below:

- 1. The owner or operator of the source shall arrange for air emission testing protocols to be provided to the Director prior to air pollution testing. Testing protocols are not required to be pre-approved by the Director prior to air pollution testing. The Director shall review air emission testing protocols for pre-approval prior to testing if requested by the owner or operator at least **45 days** before conducting the test.
- 2. Any person proposing to conduct an emissions test to demonstrate compliance with an applicable standard shall notify the Director at least **15 days** before beginning the test so that the Director may at his option observe the test.
- 3. The owner or operator of the source shall arrange for controlling and measuring the production rates during the period of air testing. The owner or operator of the source shall ensure that the equipment or process being tested is operated at the production rate that best fulfills the purpose of the test. The individual conducting the emission test shall describe the procedures used to obtain accurate process data and include in the test report the average production rates determined during each testing period.
- 4. Two copies of the final air emission test report shall be submitted to the Director not later than **30 days** after sample collection unless otherwise specified in the specific conditions. The owner or operator may request an extension to submit the final test report. The Director shall approve an extension request if he finds that the extension request is a result of actions beyond the control of the owner or operator.
  - a. The Director shall make the final determination regarding any testing procedure deviation and the validity of the compliance test. The Director may:
    - i. Allow deviations from a method specified under a rule in this Section if the owner or operator of the source being tested demonstrates to the satisfaction of the Director that the specified method is inappropriate for the source being tested.
    - ii. Prescribe alternate test procedures on an individual basis when he finds that the alternative method is necessary to secure more reliable test data.
    - iii. Prescribe or approve methods on an individual basis for sources or pollutants for which no test method is specified in 15A NCAC 02D .2600 if the methods can be demonstrated to determine compliance of permitted emission sources or pollutants.
  - b. The Director may authorize the DAQ to conduct independent tests of any source subject to a rule in 15A NCAC 02D to determine the compliance status of that source or to verify any test data submitted relating to that source. Any test conducted by the Division of Air Quality using the appropriate testing procedures described in 15A NCAC 02D .2600 has precedence over all other tests.

#### KK. Reopening for Cause [15A NCAC 02Q .0517]

- 1. A permit shall be reopened and revised under the following circumstances:
  - a. additional applicable requirements become applicable to a facility with remaining permit term of three or more years;
  - b. additional requirements (including excess emission requirements) become applicable to a source covered by Title IV;

- c. the Director or EPA finds that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit; or
- d. the Director or EPA determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
- 2. Any permit reopening shall be completed or a revised permit issued within 18 months after the applicable requirement is promulgated. No reopening is required if the effective date of the requirement is after the expiration of the permit term unless the term of the permit was extended pursuant to 15A NCAC 02Q .0513(c).
- 3. Except for the state-enforceable only portion of the permit, the procedures set out in 15A NCAC 02Q .0507, .0521, or .0522 shall be followed to reissue the permit. If the State-enforceable only portion of the permit is reopened, the procedures in 15A NCAC 02Q .0300 shall be followed. The proceedings shall affect only those parts of the permit for which cause to reopen exists.
- 4. The Director shall notify the Permittee at least 60 days in advance of the date that the permit is to be reopened, except in cases of imminent threat to public health or safety the notification period may be less than 60 days.
- 5. Within 90 days, or 180 days if the EPA extends the response period, after receiving notification from the EPA that a permit needs to be terminated, modified, or revoked and reissued, the Director shall send to the EPA a proposed determination of termination, modification, or revocation and reissuance, as appropriate.

#### LL. Reporting Requirements for Non-Operating Equipment [15A NCAC 02Q .0508(i)(16)]

The Permittee shall maintain a record of operation for permitted equipment noting whenever the equipment is taken from and placed into operation. When permitted equipment is not in operation, the requirements for testing, monitoring, and recordkeeping are suspended until operation resumes.

#### MM. Fugitive Dust Control Requirement [15A NCAC 02D .0540]

As required by 15A NCAC 02D .0540 "Particulates from Fugitive Dust Emission Sources," the Permittee shall not cause or allow fugitive dust emissions to cause or contribute to substantive complaints or excess visible emissions beyond the property boundary. If substantive complaints or excessive fugitive dust emissions from the facility are observed beyond the property boundaries for six minutes in any one hour (using Reference Method 22 in 40 CFR, Appendix A), the owner or operator may be required to submit a fugitive dust plan as described in 02D .0540(f).

"Fugitive dust emissions" means particulate matter from process operations that does not pass through a process stack or vent and that is generated within plant property boundaries from activities such as: unloading and loading areas, process areas, stockpiles, stock pile working, plant parking lots, and plant roads (including access roads and haul roads).

#### NN. Specific Permit Modifications [15A NCAC 02Q .0501 and .0523]

- 1. For modifications made pursuant to 15A NCAC 02Q .0501(b)(2), the Permittee shall file a Title V Air Quality Permit Application for the air emission source(s) and associated air pollution control device(s) on or before 12 months after commencing operation.
- 2. For modifications made pursuant to 15A NCAC 02Q .0501(c)(2), the Permittee shall not begin operation of the air emission source(s) and associated air pollution control device(s) until a Title V Air Quality Permit Application is filed and a construction and operation permit following the procedures of Section .0500 (except for Rule .0504 of this Section) is obtained.
- 3. For modifications made pursuant to 502(b)(10), in accordance with 15A NCAC 02Q .0523(a)(1)(C), the Permittee shall notify the Director and EPA (Air Permitting Branch, EPA, Region 4, 61 Forsyth Street SW, Atlanta, GA 30303 or through the EPA CEDRI) in writing at least seven days before the change is made.
  - a. The written notification shall include:
    - i. a description of the change at the facility;
    - ii. the date on which the change will occur;
    - iii. any change in emissions; and
    - iv. any permit term or condition that is no longer applicable as a result of the change.
  - b. In addition to this notification requirement, with the next significant modification or Air Quality Permit renewal, the Permittee shall submit a page "E5" of the application forms signed by the responsible official verifying that the application for the 502(b)(10) change/modification, is true, accurate, and complete. Further note that modifications made pursuant to 502(b)(10) do not relieve the Permittee from satisfying preconstruction requirements.

Permit 03700T24 Page 32

#### OO. Third Party Participation and EPA Review [15A NCAC 02Q .0521, .0522 and .0525(7)]

For permits modifications subject to 45-day review by the federal EPA, EPA's decision to not object to the proposed permit is considered final and binding on the EPA and absent a third party petition, the failure to object is the end of EPA's decision-making process with respect to the revisions to the permit. The time period available to submit a public petition pursuant to 15A NCAC 02Q .0518 begins at the end of the 45-day EPA review period.