# Drinking Water Protection Program

# **OVERVIEW**

The Federal Safe Drinking Water Act (SDWA) Amendments of 1996 emphasize pollution prevention as an important strategy for the protection of ground and surface water resources. This new focus promotes the prevention of drinking water contamination as a cost-effective means to provide reliable, long-term and safe drinking water sources for public water supply (PWS) systems. In order to determine the susceptibility of public water supply sources to contamination, the amendments also required that all states establish a Source Water Assessment Program (SWAP). Specifically, Section 1453 of the SDWA Amendments require that states develop and implement a SWAP to:

- Delineate source water assessment areas;
- Inventory potential contaminants in these areas; and
- Determine the susceptibility of each public water supply to contamination.

In North Carolina, the agency responsible for the SWAP is the NC DENR DWR's Drinking Water Protection Program. The SWAP Plan was approved from EPA in November 1999. The SWAP Plan, entitled North Carolina's Source Water Assessment Program Plan, fully describes the methods and procedures used to delineate and assess the susceptibility of more than 9,000 wells and approximately 207 surface water intakes. To review the SWAP Plan, visit the PWS Section website at <a href="http://ncwater.org/?page=63">http://ncwater.org/?page=63</a>.

# DELINEATION OF SOURCE WATER ASSESSMENT AREAS

The SWAP Plan builds upon existing protection programs for ground and surface water resources. These include the state's Wellhead Protection Program and the Water Supply Watershed Protection Program.

# WELLHEAD PROTECTION (WHP) PROGRAM

North Carolinians withdraw more than 88 million gallons of groundwater per day from more than 9,000 water supply wells across the state. In 1986, Congress passed Amendments to the SDWA requiring states to develop wellhead protection programs that reduce the threat to the quality of groundwater used for drinking water by identifying and managing recharge areas to specific wells or wellfields.

Defining a wellhead protection area (WHPA) is one of the most critical components of wellhead protection. A WHPA is defined as "the surface and subsurface area surrounding a water well or wellfield, supplying a public water system, through which contaminants are reasonably likely to move toward and reach such water well or wellfield." The SWAP uses the methods described in the state's approved WHP Program to delineate source water assessment areas for all public water supply wells. More information related to North Carolina's WHP Program can be found at http://ncwater.org/?page=147.

# WATER SUPPLY WATERSHED PROTECTION (WSWP) PROGRAM

DWR is responsible for managing the standards and classifications of all water supply watersheds. In 1992, the WSWP Rules were adopted by the EMC and require all local governments that have land use jurisdiction within water supply watersheds to adopt and implement water supply watershed protection ordinances, maps and management plans. SWAP uses the established water supply watershed boundaries and methods established by the WSWP program as a basis to delineate source water assessment areas for all public water surface water intakes. Additional information regarding the WSWP Program can be found at <a href="http://portal.ncdenr.org/web/wq/ps/csu">http://portal.ncdenr.org/web/wq/ps/csu</a>.

# Susceptibility Determination - North Carolina's Overall Approach

The SWAP Plan contains a detailed description of the methods used to assess the susceptibility of each PWS intake in North Carolina. The following is a brief summary of the susceptibility determination approach.

#### **Overall Susceptibility Rating**

The overall susceptibility determination rates the potential for a drinking water source to become contaminated. The overall susceptibility rating for each PWS intake is based on two key components: a contaminant rating and an inherent vulnerability rating. For a PWS to be determined "susceptible", a potential contaminant source must be present and the existing conditions of the PWS intake location must be such that a water supply could become contaminated. The determination of susceptibility for each PWS intake is based on combining the results of the inherent vulnerability rating and the contaminant rating for each intake. Once combined, a PWS is given a susceptibility rating of higher, moderate or lower (H, M or L).

### Inherent Vulnerability Rating

Inherent vulnerability refers to the physical characteristics and existing conditions of the watershed or aquifer. The inherent vulnerability rating of groundwater intakes is determined based on an evaluation of aquifer characteristics, unsaturated zone characteristics and well integrity and construction characteristics. The inherent vulnerability rating of surface water intakes is determined based on an evaluation of the watershed classification (WSWP Rules), intake location, raw water quality data (e.g., turbidity and total coliform) and watershed characteristics (e.g., average annual precipitation, land slope, land use, land cover, groundwater contribution).

#### **Contaminant Rating**

The contaminant rating is based on an evaluation of the density of potential contaminant sources (PCSs), their relative risk potential to cause contamination, and their proximity to the water supply intake within the delineated assessment area.

#### <u>Inventory of Potential Contaminant Sources (PCSs)</u>

In order to inventory PCSs, the SWAP conducted a review of relevant, available sources of existing data at federal, state and local levels. The SWAP selected sixteen statewide databases that were attainable and contained usable geographic information related to PCSs.

# Source Water Protection

The PWS Section believes that the information from the source water assessments are the basis for future initiatives and priorities for public drinking water source water protection (SWP) activities. The PWS Section encourages all PWS system owners to implement efforts to manage identified sources of contamination and to reduce or eliminate the potential threat to drinking water supplies through locally implemented protection planning.

To encourage and support local SWP, the state offers PWS system owners assistance with local SWP planning as well as materials such as:

- Fact sheets outlining sources of funding and other resources for local SWP efforts.
- Success stories describing local SWP efforts in North Carolina.
- Guidance about how to incorporate SWAP and SWP information in Consumer Confidence Reports (CCRs).

# **Public Water Supply Susceptibility Determinations**

In April 2004, the PWS Section completed source water assessments for all drinking water sources and generated reports for the PWS systems using these sources. The assessments are updated regularly; the most recent updates were published in July 2014. The results of the assessments can be viewed in two different ways, either through the interactive ArcIMS mapping tool or compiled in a written report for each PWS system. To access the ArcIMS mapping tool, simply click on the "NC SWAP Info" icon on the web page: <a href="http://ncwater.org/?page=102">http://ncwater.org/?page=102</a>. To view a report, click on the SWAP Reports icon on: <a href="http://ncwater.org/?page=102">http://ncwater.org/?page=102</a>. and enter in the PWS system name for the system of interest.

In the Tar-Pamlico River Basin, 378 public water supply sources were assessed. Nine are surface water sources and 369 are groundwater sources. Of the 369 groundwater sources, 23 of them have a Higher, 290 have a Moderate and 56 have a Lower susceptibility rating. Table 1 identifies the surface water sources and their overall susceptibility ratings. It is important to note that a susceptibility rating of Higher does not imply poor water quality. Susceptibility is an indication of a water supply's potential to become contaminated.

TABLE 1: SWAP RESULTS FOR SURFACE WATER SOURCES IN THE TAR-PAMLICO RIVER BASIN

PWS ID Number	INHERENT VULNERABILITY RATING	CONTAMINANT RATING	OVERALL SUSCEPTIBILITY RATING	Name of Surface Water Source	PWS NAME
0235010	M	L	M	Cedar Creek	Town of Franklinton
0235010	M	L	М	Taylor Creek	Town of Franklinton
0235015	Н	M	Н	Tar River	Town of Louisburg
0433010	Н	M	Н	Tar River	Town of Tarboro
0464010	Н	M	Н	Tar River at Sunset	City of Rocky Mount
0464010	М	М	М	Tar River at Reservoir	City of Rocky Mount
0442025	Н	L	M	Fishing Creek	Enfield Water System
0474010	Н	М	Н	Tar River	Greenville Utilities Commission
0498010	Н	М	Н	Tar River	City of Wilson